

Sphere-Constrained ML Detection for Frequency-Selective Channels

H. Vikalo, B. Hassibi, and U. Mitra, *Senior Member, IEEE*

Abstract—The maximum-likelihood (ML) sequence detection problem for channels with memory is investigated. The Viterbi algorithm (VA) provides an exact solution. Its computational complexity is linear in the length of the transmitted sequence, but exponential in the channel memory length. On the other hand, the sphere decoding (SD) algorithm also solves the ML detection problem exactly, and has expected complexity which is a low-degree polynomial (often cubic) in the length of the transmitted sequence over a wide range of signal-to-noise ratios. We combine the sphere-constrained search strategy of SD with the dynamic programming principles of the VA. The resulting algorithm has the worst-case complexity determined by the VA, but often significantly lower expected complexity.

Index Terms—Expected complexity, frequency-selective channels, maximum-likelihood (ML) sequence detection, sphere decoding, Viterbi algorithm (VA).

I. INTRODUCTION

WE consider the frequency-selective channel model, with input/output relation given by

$$x_i = \sum_{j=1}^l h_j s_{i-j+1} + v_i \quad (1)$$

where $h_i, i = 1, \dots, l$ are the coefficients of the channel impulse response, l denotes the channel length, s_i is the i th symbol in the transmitted sequence chosen from an L -pulse amplitude modulation (PAM) constellation $\mathcal{D}_L = \{-(L-1)/2, \dots, (L-1)/2\}$, and v_i denotes a Gaussian noise sample $\mathcal{N}(0, \sigma^2)$. Over a horizon of length T , the maximum-likelihood (ML) sequence detector minimizes the cost function

$$\mathcal{C}_T = \sum_{k=1}^T \left| x_k - \sum_{m=1}^l h_m s_{k-m+1} \right|^2 \quad (2)$$

to find the most likely transmitted symbol sequence $\{s_1, \dots, s_T\}$. The Viterbi algorithm (VA) [1] exploits the Markovian property of the channel, and finds the sequence which minimizes \mathcal{C}_T by using dynamic programming ideas. Typically, the VA is employed as a breadth-first search on a trellis, a directed graph describing systems with memory, illustrated in Fig. 1. The key observation is that \mathcal{C}_T can be

Paper approved by B. Hochwald, the Editor for MIMO Techniques of the IEEE Communications Society. Manuscript received April 2, 2004; revised December 14, 2004. This work was supported in part by the National Science Foundation under Grant CCR-0133818, and in part by the Office of Naval Research under Grant N00014-02-1-0578. This paper was presented in part at the 37th Asilomar Conference on Signals, Systems, and Computers, Pacific Grove, CA, November 2003, and in part at the IEEE International Conference on Acoustics, Speech, and Signal Processing, Hong Kong, April 2003.

H. Vikalo and B. Hassibi are with the Department of Electrical Engineering, California Institute of Technology, Pasadena, CA 91125 USA (e-mail: hvikalo@systems.caltech.edu).

U. Mitra is with the Department of Electrical Engineering, University of Southern California, Los Angeles, CA 90089 USA.

Digital Object Identifier 10.1109/TCOMM.2006.877946




Fig. 1. Trellis with four states. The “empty” nodes indicate states which violate the sphere constraint and are thus pruned by the combined VA/SD. For instance, as indicated above, $\mathcal{C}_3(S_3^{[2]}) > r^2$.

recursively computed as

$$\mathcal{C}_{k+1} = \mathcal{C}_k + \left| x_{k+1} - \sum_{m=1}^l h_m s_{k-m+1} \right|^2, \quad k = 0, \dots, T-1, \mathcal{C}_0 = 0. \quad (3)$$

Clearly, the second term on the right-hand side (RHS) of (3) does not depend on s_{k-l}, \dots, s_1 , but only on the current symbol s_k and the current memory of the channel $s_{k-1}s_{k-2} \dots s_{k-l+1}$. The L^{l-1} possible states of the channel memory comprise the state set \mathcal{S}_k (see Fig. 1). To find the k th segment of the optimal path, it is sufficient, for every state $S_{k+1}^{[j]} \in \mathcal{S}_{k+1}$ ($j = 1, \dots, L^{l-1}$), to keep only the branch emanating from a state in \mathcal{S}_k and terminating in the state $S_{k+1}^{[j]}$ that has the smallest transition cost. This procedure can be done recursively. The trellis path of length T that has the smallest cost \mathcal{C}_T is the optimal path. The signal sequence that corresponds to the branch transitions along the optimal trellis path is the solution to the ML detection problem. The complexity of the VA is proportional to the number of states, and thus grows exponentially with the length of the channel. On the other hand, it is linear in the length of the data sequence.

The sphere decoding (SD) algorithm [2] can also be used for detection on channels with memory [3], [4]. Permitting a guard interval, the SD algorithm provides ML performance. To employ SD, we first need to write (1) as

$$\mathbf{x} = H\mathbf{s} + \mathbf{v}$$

where the $(T+l-1) \times 1$ vectors \mathbf{x} and \mathbf{v} , the $(T+l-1) \times T$ matrix H , and the $T \times 1$ vector \mathbf{s} are given by

$$\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_{T+l-1} \end{bmatrix}, \quad \mathbf{v} = \begin{bmatrix} v_1 \\ v_2 \\ \vdots \\ v_{T+l-1} \end{bmatrix}$$

$$H = \begin{bmatrix} h_1 & & & & \\ \vdots & \ddots & & & \\ h_l & \cdots & h_1 & & \\ & & \ddots & & \\ & & & h_l & \end{bmatrix}, \quad \mathbf{s} = \begin{bmatrix} s_1 \\ \vdots \\ s_T \end{bmatrix}. \quad (4)$$

The ML detection can now be expressed as an integer least-squares problem

$$\min_{\mathbf{s} \in \mathcal{D}_L^T} \|\mathbf{x} - H\mathbf{s}\|^2. \quad (5)$$

This problem has a geometric interpretation: given a point \mathbf{x} , find the closest lattice point in a skewed lattice $H\mathbf{s}$. The SD algorithm solves (5) by performing a search over only those points $H\mathbf{s}$ that belong to a sphere around \mathbf{x} . The radius r of the sphere is chosen so that we find a point inside the sphere with a high probability. We assume that the noise samples v_1, v_2, \dots, v_T are independent and identically distributed (i.i.d.); hence $\|\mathbf{x} - H\mathbf{s}\|^2 = \|\mathbf{v}\|^2 = v_1^2 + \dots + v_T^2$ is a chi-square random variable with T degrees of freedom. Thus, the radius $r^2 = \alpha T \sigma^2$ can be chosen probabilistically so that

$$\int_0^{\alpha T} \frac{\lambda^{T/2-1}}{\Gamma(T)} e^{-\lambda} d\lambda = 1 - \epsilon \quad (6)$$

where $\epsilon \ll 1$. The condition that a point $H\mathbf{s}$ belongs to the sphere of radius r is given by

$$r^2 \geq \|\mathbf{x} - H\mathbf{s}\|^2. \quad (7)$$

The summation on the RHS of (7) can be expanded to yield a set of conditions on the components of \mathbf{s}

$$(x_1 - h_1 s_1)^2 \leq r_1^2, (x_2 - h_1 s_2 - h_2 s_1)^2 \leq r_2^2, \\ (x_3 - h_1 s_3 - h_2 s_2 - h_3 s_1)^2 \leq r_3^2, \text{ etc.}$$

where $r_1^2 = r^2$, $r_2^2 = r_1^2 - (x_1 - h_1 s_1)^2$, $r_3^2 = r_2^2 - (x_2 - h_1 s_2 - h_2 s_1)^2$, etc. Note that this gives T conditions on the components of \mathbf{s} which are necessary, but still not sufficient. Only if the additional constraint

$$r_{T+1}^2 \geq (x_{T+1} - h_1 s_{T-l+2} - \dots - h_2 s_T)^2 + \dots \\ + (x_{T+l-1} - h_l s_T)^2$$

where $r_{T+1}^2 = r^2 - \sum_{j=1}^T (x_j - \sum_{m=1}^l h_m s_{j-m+1})^2$ is satisfied, does the point \mathbf{s} indeed belong to the sphere, i.e., satisfies condition (7). The SD algorithm performs a depth-first search on a tree, as illustrated in Fig. 2. A trace leading to a surviving node on the k th level of the tree corresponds to a vector $[s_1 \dots s_k]^*$ inside the k -dimensional sphere. With the probabilistic choice of r , the computational complexity of the SD algorithm is a random variable [5], with the mean often significantly below the complexity of the VA [4].

II. COMBINING SD AND VA

The complexity of the VA is linear in the length of the data sequence, but is exponential in the channel memory size, where the base of the exponent is the symbol alphabet size. Thus, for long channels and/or large symbol alphabets, the VA is often inefficient and occasionally nonfeasible. On the other hand, over a wide range of signal-to-noise ratios (SNRs), the expected complexity of SD is a low-degree polynomial in the data block length, and the degree of the polynomial does not




Fig. 2. Tree-search interpretation of the SD algorithm. The “empty” node indicates a lattice point which is inside a 4-D sphere, but violates corresponding state constraint (i.e., $\mathcal{C}_4(\cdot)$ corresponding to this point is not the smallest one), and is thus pruned by the combined SD/VA.

vary significantly with the channel memory size. However, the worst-case complexity of SD is exponential in the data block length. Furthermore, the SD algorithm does not at all exploit the Markovian property of the channel, which is precisely what the VA does. Therefore, a hybrid receiver structure that combines the constrained search strategy of SD with the trellis-based decoding of the VA is desired. This can be obtained by either modifying the SD algorithm to include the channel memory state constraints or by adding the sphere constraints to the trellis search of the VA. The two approaches, essentially equivalent, although one is depth-first and the other is breadth-first, are briefly presented here.

Algorithm 1 [SD Modified with VA]: Consider the SD algorithm and the tree search illustrated in Fig. 1. The SD algorithm does not take into account the Markovian property of the channel. We propose the following modification. Assume that the algorithm is currently examining a node on the k th level of the tree. Based on the current, and on up to $l-2$ tree nodes on levels $k-1, k-2, \dots, k-l+1$, along which the algorithm descended to the current node, we identify the current state $\mathcal{S}_k^{[j]} = s_k s_{k-1} \dots s_{k-l+1}$. The meaning of the state is the same as on the trellis, i.e., it is the current state of the channel memory and we assign a cost $\mathcal{C}_k(\mathcal{S}_k^{[j]})$ to it. By writing out the recursion for r_k^2 , it is easy to see that

$$\mathcal{C}_k(\mathcal{S}_k^{[j]}) = r^2 - r_{k+1}^2.$$

Now, in addition to the standard steps that the SD algorithm undertakes, we enforce that it also compares this $\mathcal{C}_k(\mathcal{S}_k^{[j]})$ with the previously stored minimum cost $\min \mathcal{C}_k(\mathcal{S}_k^{[j]})$. If the current $\mathcal{C}_k(\mathcal{S}_k^{[j]})$ is greater than $\min \mathcal{C}_k(\mathcal{S}_k^{[j]})$, the algorithm prunes the tree, i.e., it discards the current tree node. If the current $\mathcal{C}_k(\mathcal{S}_k^{[j]})$ is smaller than the previously stored $\min \mathcal{C}_k(\mathcal{S}_k^{[j]})$ (or there are no previously stored $\min \mathcal{C}_k(\mathcal{S}_k^{[j]})$'s), the algorithm assigns $\min \mathcal{C}_k(\mathcal{S}_k^{[j]}) := \mathcal{C}_k(\mathcal{S}_k^{[j]})$ and proceeds with the other SD steps. Note that the algorithm is still depth-first. Clearly, its complexity will be lower than the complexity of the original SD, at the expense of additional storage requirements. \square

Algorithm 2 [VA Modified with SD]: Consider the trellis representation of a frequency-selective channel and a finite data block transmission. We impose the constraint (7) that the transmitted signal belongs to a sphere of radius r defined by (6). As we have shown in the previous section, an obvious necessary condition that the transmitted signal needs to satisfy is given by

while the $d \times l$ dimensional matrices Σ_t and Σ_a are given by

$$\Sigma_t = \begin{bmatrix} s_{t,1} & & & 0 \\ \vdots & \ddots & & \\ s_{t,d-l+1} & \cdots & s_{t,d-2l} & \\ \vdots & & & \vdots \\ s_{t,d} & \cdots & s_{t,d-l+1} & \\ \vdots & & & \vdots \\ s_{a,1} & & & 0 \\ \vdots & \ddots & & \\ s_{a,d-l+1} & \cdots & s_{a,d-2l} & \\ \vdots & & & \vdots \\ \Sigma_{a,-\frac{L-1}{2}} & & & s_{a,d-l+1} \end{bmatrix}$$

where the $\Sigma_{a,-(L-1)/2}$ region in Σ_a has all entries equal to $-(L-1)/2$. The vector $[\mathbf{v} \mathbf{h}]^*$ in (11) is Gaussian, and hence, we can find the characteristic function of $\|\mathbf{v} + (\Sigma_t - \Sigma_a)\mathbf{h}\|^2$ (see [4])

$$\Phi(\omega) = \frac{\sqrt{2^{d+l}}}{\sqrt{(1+j\omega 2\sigma^2)^{d-l} \prod_{i=1}^l [1+j\omega 2(\sigma^2 + \rho_i)]}}$$

where $\rho_i, i = 1, \dots, l$ are the eigenvalues of the matrix $(\Sigma_t - \Sigma_a)^*(\Sigma_t - \Sigma_a)$. Thus, for a given $(\mathbf{s}_t; \mathbf{s}_{a,\text{past}})$, the probability that the state $\mathcal{S}_d^{[1]}$ corresponding to $\mathbf{s}_{a,\text{state}} = [-(L-1)/2 \dots -(L-1)/2]$ survives is given by

$$P\left(\mathcal{C}_d\left(\mathcal{S}_d^{[1]}\right) \leq r_d^2 \mid \mathbf{s}_t, \mathbf{s}_{a,\text{past}}\right) = \frac{1}{2\pi} \int_{t=0}^{r^2} \int_{\omega=-\infty}^{\infty} \Phi(\omega) e^{-j\omega t} d\omega dt. \quad (12)$$

To find the probability $P(\mathcal{C}_d(\mathcal{S}_d^{[1]}) \leq r_d^2)$, we need to average (12) over all $(\mathbf{s}_t; \mathbf{s}_{a,\text{past}})$

$$P\left(\mathcal{C}_d\left(\mathcal{S}_d^{[1]}\right) \leq r_d^2\right) = \frac{1}{L^{l-1}} \frac{1}{L^{2(d-l+1)}} \sum_{\mathbf{s}_{t,\text{state}}} \sum_{(\mathbf{s}_{t,\text{past}}; \mathbf{s}_{a,\text{past}})} \frac{1}{2\pi} \times \int_{t=0}^{r^2} \int_{\omega=-\infty}^{\infty} \Phi(\omega) e^{-j\omega t} d\omega dt. \quad (13)$$

The outer summation in (13) is performed over L^{l-1} states in which the transmitted sequence may terminate. The inner summation is performed over $L^{2(d-l+1)}$ possible pairs $(\mathbf{s}_{t,\text{past}}; \mathbf{s}_{a,\text{past}})$. An efficient enumeration of the symbol sequences that might ease the computation (13) by counting pairs $(\mathbf{s}_t; \mathbf{s}_{a,\text{past}})$ with the same $P(\mathcal{C}_d(\mathcal{S}_d^{[1]}) \leq r_d^2 \mid \mathbf{s}_t, \mathbf{s}_{a,\text{past}})$ and lead to a more explicit closed-form expression for $P(\mathcal{C}_d(\mathcal{S}_d^{[1]}) \leq r_d^2)$, so far appears hard to obtain. Thus, we leave (13) in its current form to be used numerically in evaluating (9) and (10).

IV. SIMULATION RESULTS AND SUMMARY

We consider a channel of length $l = 6$, transmitting 4-phase-shift keying (PSK)-modulated ($L = 4$) data in blocks of length $T = 20$, and employ the combined VA/SD for ML detection at the receiver. Let us define the complexity exponent as $e =$




Fig. 3. Expected complexity exponents as a function of SNR for the VA, the SD, and the combined VA/SD, $l = 6, T = 20, L = 4$.




Fig. 4. Probability density function (empirical) of the complexity exponent of the combined VA/SD algorithm, $l = 6, T = 20, L = 4, \text{SNR} = 18 \text{ dB}$. The dashed line denotes complexity exponent of the VA.

$\log_T F$, where F denotes the total number of operations (flop count) performed when detecting \mathbf{s} . Fig. 3 shows the (empirically obtained) expected complexity exponent as a function of SNR. In the considered SNR range, the combined algorithm has lower expected complexity than both the SD and the VA. Furthermore, the expected complexity is roughly cubic in the considered range of SNR. If we further decrease SNR, the expected complexity of the combined algorithm increases; however, it is bounded above by the complexity of the VA.

Fig. 4 shows empirical distribution of the complexity exponent at $\text{SNR} = 18 \text{ dB}$. The complexity is for the scheme that finds the optimal solution. In particular, we set the sphere radius so that a point is found with probability .9; if no point is found, we increase this probability to .99, and so on. As evident from Fig. 4, the complexity exponent of the VA/SD algorithm

is often significantly smaller than the complexity exponent corresponding to the VA (denoted by the vertical dashed line).

In summary, we proposed combining the sphere-constrained search of the SD and the dynamic programming principles of the VA for ML detection for channels with memory. The hybrid algorithm is either the SD modified to speed up the search for the closest point in the lattice, or the VA with the imposed sphere constraints resulting in state reduction on the trellis. We found the analytic expression for the expected complexity of the algorithm and illustrated it via simulations. The algorithm has expected complexity which is polynomial in the data block length over a wide range of SNRs.

REFERENCES

- [1] A. D. Viterbi, "Error bounds for convolutional codes and an asymptotically optimum decoding algorithm," *IEEE Trans. Inf. Theory*, vol. IT-13, no. 1, pp. 260–269, Jan. 1967.
- [2] U. Fincke and M. Pohst, "Improved methods for calculating vectors of short length in a lattice, including a complexity analysis," *Math. Comput.*, vol. 44, pp. 463–471, Apr. 1985.
- [3] W. H. Mow, "Maximum-likelihood sequence estimation from the lattice viewpoint," *IEEE Trans. Inf. Theory*, vol. 40, no. 9, pp. 1591–1600, Sep. 1994.
- [4] H. Vikalo and B. Hassibi, "On the sphere decoding algorithm. II. Generalizations, second-order statistics, and applications to communications," *IEEE Trans. Signal Process.*, vol. 53, no. 8, pp. 2819–2834, Aug. 2005.
- [5] B. Hassibi and H. Vikalo, "On the sphere decoding algorithm. I. Expected complexity," *IEEE Trans. Signal Process.*, vol. 53, no. 8, pp. 2806–2818, Aug. 2005.
- [6] S. J. Simmons, "Breadth-first trellis decoding with adaptive effort," *IEEE Trans. Commun.*, vol. 38, no. 1, pp. 3–12, Jan. 1990.
- [7] H. Zamiri-Jafarian and S. Pasupathy, "Complexity reduction of the MLS/MLSDE receiver using the adaptive state allocation algorithm," *IEEE Trans. Wireless Commun.*, vol. 1, no. 1, pp. 101–111, Jan. 2002.