Sensitivity and Discovery Potential of nEXO to Neutrinoless Double Beta Decay

J. B. Albert, G. Anton, I. J. Arnquist, I. Badhrees, P. Barbeau, D. Beck, V. Belov, F. Bourque, J. P. Brodsky, E. Brown, T. Brunner, L. 2 A. Burenkov, G. F. Cao, L. C

¹Department of Physics and CEEM, Indiana University, Bloomington, IN 47405 Erlangen Centre for Astroparticle Physics (ECAP), Friedrich-Alexander University Erlangen-Nürnberg, Erlangen 91058, Germany ³Pacific Northwest National Laboratory, Richland, WA 99352 ⁴Department of Physics, Carleton University, Ottawa, Ontario K1S 5B6, Canada ⁵Department of Physics, Duke University, and Triangle Universities Nuclear Laboratory (TUNL), Durham, North Carolina 27708 ⁶Physics Department, University of Illinois, Urbana-Champaign, IL 61801 ⁷Institute for Theoretical and Experimental Physics, Moscow, Russia ⁸ Université de Sherbrooke, Sherbrooke, Québec J1K 2R1, Canada ⁹Lawrence Livermore National Laboratory, Livermore, CA 94550 ¹⁰Department of Physics, Applied Physics and Astronomy, Rensselaer Polytechnic Institute, Troy, NY 12180 ¹¹Physics Department, McGill University, Montréal, Québec, Canada ¹²TRIUMF, Vancouver, British Columbia V6T 2A3, Canada ¹³Institute of High Energy Physics, Beijing, China ¹⁴Institute of Microelectronics, Beijing, China ¹⁵Physics Department, Colorado State University, Fort Collins, Colorado 80523
¹⁶Brookhaven National Laboratory, Upton, New York 11973 ¹⁷Department of Physics, Laurentian University, Sudbury, Ontario P3E 2C6 Canada ¹⁸SLAC National Accelerator Laboratory, Menlo Park, California 94025 ¹⁹Physics Department, Stanford University, Stanford, California 94305-4060 ²⁰Department of Physics, University of South Dakota, Vermillion, South Dakota 57069 ²¹Department of Physics and Astronomy, University of Alabama, Tuscaloosa, AL 35487 ²²Department of Physics, Drexel University, Philadelphia, Pennsylvania 19104 ²³Oak Ridge National Laboratory, Oak Ridge, TN 37831 ²⁴ Amherst Center for Fundamental Interactions and Physics Department, University of Massachusetts, Amherst, MA 01003 ²⁵Department of Physics, Yale University, New Haven, CT 06511 ²⁶Department of Physics and Astronomy, Stony Brook University, SUNY, Stony Brook, New York 11794 ²⁷ IBS Center for Underground Physics, Daejeon 34047, Korea ²⁸Kellogg Lab, Caltech, Pasadena, California 91125 ²⁹LHEP, Albert Einstein Center, University of Bern, Bern, Switzerland (Dated: October 17, 2017)

The next-generation Enriched Xenon Observatory (nEXO) is a proposed experiment to search for neutrinoless double beta $(0\nu\beta\beta)$ decay in 136 Xe with a target half-life sensitivity of approximately 10^{28} years using 5×10^3 kg of isotopically enriched liquid-xenon in a time projection chamber. This improvement of two orders of magnitude in sensitivity over current limits is obtained by a significant increase of the 136 Xe mass, the monolithic and homogeneous configuration of the active medium, and the multi-parameter measurements of the interactions enabled by the time projection chamber. The detector concept and anticipated performance are presented based upon demonstrated realizable background rates.

I. INTRODUCTION

The observation of neutrinoless double beta $(0\nu\beta\beta)$ decay would reveal fascinating new physics by demonstrating lepton number violation and confirming the existence of elementary Majorana fermions [1]. This could impact our understanding of the neutrino mass generation mechanisms and may help illuminate possible origins of the cosmic baryon asymmetry [2]. Potential for discovery underpins the motivation for pursuing the ambitious experimental program described in this article.

Indeed, this is the same type of discovery quest that drives the construction of large accelerators to probe higher energies or that triggers the construction of larger telescopes capable of peering deeper in to the universe. This exciting opportunity has gained widespread interest following the discovery of neutrino oscillations [3–5] that prove neutrino masses are not all zero. Indeed the difference between Majorana and Dirac neutrinos is only observable in the case of non-zero neutrino mass.

While discovery of Majorana neutrinos and leptonnumber violation is the principal goal, the discovery of $0\nu\beta\beta$ decay provides useful information on neutrino mass values, even if systematic uncertainties deriving from nuclear physics and the particular mechanism responsible for the decay obscure the translation from a measured half-life into an effective Majorana mass. In this context, $0\nu\beta\beta$ discovery requirements are often represented in the parameter space of the effective Majorana neutrino mass $\langle m_{\beta\beta} \rangle$ versus the mass of the lightest neutrino eigenstate, where

$$\langle m_{\beta\beta} \rangle = \left| \sum_{i=1}^{3} U_{ei}^{2} m_{i} \right| \tag{1}$$

and m_i are the neutrino mass eigenvalues and U_{ei} the mixing matrix elements. The experimentally observable

 $0\nu\beta\beta$ decay half-life is inversely proportional to $\langle m_{\beta\beta}\rangle^2$:

$$[T_{1/2}^{0\nu}]^{-1} = \frac{\langle m_{\beta\beta} \rangle^2}{m_e^2} G^{0\nu} |M^{0\nu}|^2 \tag{2}$$

where m_e stands for the electron mass, $G^{0\nu}$ is the phase space factor, and $M^{0\nu}$ the nuclear matrix elements. This treatment assumes that $0\nu\beta\beta$ is mediated by the exchange of a light Majorana neutrino [6]. While the effective Majorana mass is useful for the comparison of sensitivities of experiments studying different nuclides, care must be taken to account for uncertainties in the axial-vector coupling constant and nuclear matrix elements. Recent work [7, 8] tried to quantify the $0\nu\beta\beta$ discovery potential for different nuclides and starting assumptions.

Among the candidate double-beta-decaying nuclei [9], $^{136}\mathrm{Xe}$ is particularly attractive. The $0\nu\beta\beta$ Q-value is high at $Q_{\beta\beta}=2458.07\pm0.31$ keV [10, 11]. Xenon reserves in the atmosphere are practically unlimited and commercial production is sufficient to support large scale experiments. As a noble gas, isotopic enrichment can be performed efficiently. Xenon is readily purified of chemical contaminants, resulting in exceedingly low intrinsic radioactive backgrounds [12, 13] and very long electron life-time [14, 15]. As a radiation detector medium, liquid xenon shows high scintillation and charge yield [16]. The high density ($\sim 3~\mathrm{g/cm^3}$) and high atomic number (Z = 54), result in short attenuation lengths for γ radiation. Finally, the xenon supply can be recycled into upgraded detectors as technology improves.

The current most stringent limit on $0\nu\beta\beta$ decay in 136 Xe is $T_{1/2}^{0\nu} > 1.07 \times 10^{26}$ y at 90% C.L. from the KamLAND-Zen experiment [17], with a corresponding sensitivity of 5.6×10^{25} y from 504 kg·y exposure. The diagnostic power of the liquid xenon (LXe) time projection chamber (TPC) allows the EXO-200 experiment [14], with a substantially smaller exposure of 178 kg·y, to reach a competitive sensitivity of 3.7×10^{25} y [18].

nEXO, a follow-on to the EXO-200 program, is a proposed next-generation $0\nu\beta\beta$ experiment utilizing 5000 kg of isotopically enriched liquid xenon in a TPC. The TPC's multi-parameter measurement capability allows the simultaneous determination of event energy, position, site multiplicity, and particle type. This capability, combined with the use of a large homogeneous detector volume, allows the optimal determination of the $0\nu\beta\beta$ signal and backgrounds while utilizing the entire xenon mass. An inherent low-background detector design results from the deliberative evaluation and choice of materials, un-

^a also at SNOLAB, Ontario, Canada

b now at Department of Physics and Physical Oceanography, UNC Wilmington, Wilmington, NC 28403

^c now at the University of California, Davis

^d now at Argonne National Lab

^e now at Lawrence Berkeley National Lab

f now at Laurentian University, Subdury, Canada

g Email: sangiorgio1@llnl.gov

^h now at OneBridge Solutions, Boise, ID

i now at Tsinghua University, Beijing, China

derground location, and the use of a layered scheme of passive and active shielding.

The multi-parameter measurement of each event is an essential feature of a homogeneous detector with dimensions (of order of 100 cm) substantially larger than the attenuation length (of order of 10 cm) of γ -rays of energy similar to the $0\nu\beta\beta$ decay Q-value. The multiparameter event signature, allowing to "resolve" a signal in more than one parameter, and the option of validating an observation through running with natural xenon, makes nEXO unique in its ability to discover a $0\nu\beta\beta$ signature. Measurement by means of multi-variable observations going beyond a one-dimensional peak search is an essential aspect of any believable discovery. This important point is often overlooked when experiments are discussed in terms of a one-dimensional rate analysis, where a low background is the only tool to perform a sensitive search. While low background is still very important, a logical question to ask is: how low does it need to be if several attributes can be determined simultaneously? In particular, the power of a multi-parameter experiment such as nEXO may substantially reduce risk, by allowing for a design that involves material purities already demonstrated at the time of the detector design.

In this article we present the experiment design, and predict the sensitivity reach and discovery potential of nEXO, explicitly taking into account its multi-parameter event structure.

A brief review of the EXO-200 detector is provided in section II. This is important because the success of EXO-200 does more than validate the generic concept of nEXO. In fact, the background in nEXO and the sensitivity discussed here are, for the most part, projected using materials whose radioactive contaminations were already tested in EXO-200. The larger detector size and more advanced instrumentation are the ingredients required to obtain the sensitivity presented here.

Section III introduces the conceptual design of the experiment, highlighting the novel solutions that are being investigated to enhance performance and deal with the size of a tonne-scale experiment. The simulations that are used to model the detector are introduced in Section IV.

Establishing a background model for the sensitivity calculation requires a careful assessment of the various contributions, in particular those from radioactivity in the detector materials. nEXO's approach to building the background model is based on the successful methodology developed by EXO-200 and is grounded in existing radio-assay measurements and Monte Carlo particle transport. This is discussed in section V.

A discussion of the sensitivity methodology, which is based on the frequentist approach, is presented in section VI. This is followed in section VII by the expected background budget and results for sensitivity and discovery potential.

II. EXO-200 EXPERIMENT

EXO-200 is an ongoing, 100 kg-class double beta decay experiment, conceived around 2005. It was envisaged as a tool for $\beta\beta$ discovery, but also as a test bench to develop the technology of a large, ultra-low background tracking calorimeter based on a TPC, utilizing isotopically enriched Xe. In many respects EXO-200 serves as a successful prototype for nEXO. A detailed technical description of the EXO-200 detector has been published [14].

EXO-200 has a total LXe mass of 175 kg held at a temperature of 167 K and isotopically enriched to a $^{136}\mathrm{Xe}$ abundance of 80.7% [15]. Thanks to a LXe density of 3.03 g/cm³, EXO-200 is compact, reducing the amount of low-activity materials needed to construct the device, when compared to a gas-phase detector.

A TPC, designed for simultaneous charge and light read-out, forms the heart of the experiment. The EXO-200 collaboration was the first to employ combined light and charge read-out in a LXe TPC exploiting the anti-correlation of these two energy deposition processes [19]. EXO-200 combined read-out of these two energy deposition processes allows full three-dimensional spatial reconstruction of energy deposits, and results in an energy resolution of $\sigma/Q_{\beta\beta}=1.23~\%$ [18].

EXO-200 is a double-sided cylindrical TPC, with the high voltage cathode in the middle and charge and light read-out planes on either end, perpendicular to the cylinder's axis. Each charge read-out plane consists of two sets of wires oriented at 60 degrees with respect to each other and a read-out pitch of 9 mm. The 175 nm Xe scintillation light is measured by an array of Avalanche Photo Diodes (APDs) on either end. The TPC body is made from thin electrolytic copper specially produced by Aurubis of Hamburg (Germany) to minimize the concentrations levels of naturally occurring radioactive impurities. Copper handling and storage limited its exposure to cosmic radiation.

The TPC is submerged in a bath of 4140 kg of HFE-7000 [20], an engineered 3M cryogen that remains liquid at the operating temperature. The HFE-7000 further serves as the innermost ultra-radiopure radiation shield. The HFE is contained in a double-walled, vacuum insulated copper cryostat. The xenon is continuously extracted from the TPC, evaporated, circulated through a purifier, and re-condensed to achieve an electron lifetime greater than 2 ms. The detector is installed underground at the Waste Isolation Pilot Plant (WIPP), near Carlsbad NM (USA).

The experience gained during the development and construction of EXO-200 forms one of the cornerstones of the nEXO experiment design. Background estimation and reduction play a particularly prominent role in this process. The large EXO-200 data set allows for a detailed understanding of the composition of the background that has actually been achieved. The comparison of a data-driven EXO-200 background model to the pre-data taking projections can be interpreted as an estimate of the

systematic uncertainties inherent to the approach chosen during EXO-200 construction and envisaged for nEXO.

The pre-data taking assessment of the EXO-200 background is documented in reference [14]. This assessment was based on the determination of the radioactivity content of all detector components, coupled with a GEANT3.21 based detector simulation to compute event rates. All detector components went through a detailed and comprehensive material screening and selection program [21, 22]. The EXO-200 collaboration adopted a background goal for events near the $0\nu\beta\beta$ Q-value, which in turn determined the allowable $^{60}{\rm Co},~^{232}{\rm Th}$ and $^{238}{\rm U}$ content of the detector. A similar approach was used to ensure that other background sources like external $\gamma{\rm s},~{\rm outgassed}~^{222}{\rm Rn},~{\rm muons},~{\rm and}~{\rm cosmogenic}~^{60}{\rm Co}~{\rm and}~^{137}{\rm Xe}~{\rm remained}~{\rm within}$ allowable limits. Shield design, and material screening and handling were based on these determinations.

Three papers, describing the analysis of the EXO-200 background, as derived from data, have been published [12, 21, 23]. The key traits of that analysis methodology are reviewed here as they form the basis for nEXO's sensitivity calculations.

The event-reconstruction capability of EXO-200 is utilized to categorize events into single-site (SS) and multisite (MS) classes. The former is predominantly composed of β -induced signal-like events, the latter of γ -ray induced background-like events. Point-like α -decay induced events are identified by their large scintillation to ionization signal ratio. These separations are analyzed and determined event-by-event. The EXO-200 data analysis utilizes all event sets by performing a simultaneous fit of both the SS and MS event distributions. The approach of this coupled fit method offers the advantage that signal and background can be determined simultaneously. The energy resolution, which allows to resolve multiple peaks within the decay series, provides important constraints for the background model. Further signal and background discrimination through a statistical method, is achieved by utilizing the event location. On average, γ -ray interactions occur preferentially near the detector surface. A stand-off distance (SD) parameter is defined as the distance to the nearest detector surface (excluding the central cathode) and used as a third independent fit variable. This additional analysis dimension helps refine the background model fit, which is dominated by γ -ray components.

 60 Co, 226 Ra, and 228 Th radioactive source calibration data is used to constrain a Geant4 Monte Carlo detector model. Differences between the model and source calibration data are utilized to quantify systematic uncertainties.

The tuned Monte Carlo model is used to compute probability density functions (PDFs) for all significant background contributors from all major detector components. The set of background PDFs are fit to the data, with their normalizations free floating. The resulting PDF normalizations determine the partial contributions to the overall

detector background and to the energy range where the $0\nu\beta\beta$ -peak is expected. The entire spectral, event multiplicity, and spatial information is used to determine the background for the $0\nu\beta\beta$ -search. The latter is performed by means of a likelihood-ratio analysis, comparing models with and without a $0\nu\beta\beta$ -peak present in the likelihood function.

An improved version of the EXO-200 analysis is described in [18], where additional information about the size of SS events are used to further discriminate between $0\nu\beta\beta$ decays and γ -ray scatterings. This analysis resulted in $\sim\!15\%$ sensitivity improvement over the analysis described above. Since the approach employed by EXO-200 requires detailed understanding of the electronics response, in estimating nEXO's sensitivity a similar improvement is achieved by enhancing the event localization resolution that determines the fraction of SS events, here called SS fractions. As explained in Section IV, SS fractions in nEXO were found to be two times better than that of EXO-200, and consistent with the projected readout scheme for nEXO.

A number of important conclusions follow from the EXO-200 fit results [12], and are relevant for nEXO's design and sensitivity. The composition of the EXO-200 background in particular provides guidance for nEXO planning.

The first important conclusion stems from the recognition that 23% of the EXO-200 background is due to an in-situ cosmogenic radioactive isotope: $^{137}\mathrm{Xe}$ (Q $_{\beta}=4173~\mathrm{keV}$). $^{137}\mathrm{Xe}$ is a background present throughout the LXe volume and thus is not reduced by a large monolithic detector volume. A deeper experimental location than WIPP is instead required for nEXO.

The contribution of cosmic rays to the EXO-200 background is described in [23]. 137 Xe, created by neutron capture, is the only significant cosmogenic contributor to the energy region near $Q_{\beta\beta}$. Because of its relatively long half life of 3.8 minutes and high production rate, 137 Xe decay cannot be sufficiently suppressed by the active veto detector. Detailed calculations of several other radionuclides that are cosmogenically produced, including those due to reactions on copper, yielded background contributions of less than 1% of that of 137 Xe.

Secondarily, it is important to recognize that the EXO-200 background event rate is dominated by naturally-occurring radioactive impurities present in the external components. The non-cosmogenic background originating from the xenon itself is found to be negligible. These observations have important consequences for nEXO: the large amount of xenon is best used in a homogeneous detector, making optimal use of its γ -ray detection capability and resulting in drastically different signal and background ratio for different depths in the detector. Such ratios are calculated for nEXO based on the modeling of γ -ray attenuation, which is well understood in the few MeV energy range and routinely implemented in modern radiation transport simulation packages.

Finally, the EXO-200 data show the presence of ²²²Rn

Description	Value
Liquid Xenon total mass	5109 kg
TPC xenon mass	4038 kg
Fiducial xenon mass	3740 kg
¹³⁶ Xe enrichment level	90%
TPC drift height	$125.3~\mathrm{cm}$
TPC drift diameter	$114.8~\mathrm{cm}$
Drift electric field	$400~\mathrm{V/cm}$
TPC Vessel height	130 cm
TPC Vessel diameter	$130~\mathrm{cm}$
HFE (Inner) Vessel diameter	$338~\mathrm{cm}$
Vacuum (Outer) Vessel diameter	$446~\mathrm{cm}$
Water Tank height	9 m
Water Tank diameter	10 m

TABLE I. Key parameters of the nEXO geometry.

in the LXe which results in background from the decay of $^{214}{\rm Bi.}$ A steady-state population of ${\sim}200~^{222}{\rm Rn}$ atoms was measured [12], likely arising from emanation from materials in the external xenon piping system. Only 17% of the $^{214}{\rm Bi}$ daughters of $^{222}{\rm Rn}$ decay in the LXe active volume, with the remaining 83% occurring on the cathode after the $^{222}{\rm Rn}$ daughter ions have drifted there. The majority of these decays are tagged using the $^{214}{\rm Bi-}^{214}{\rm Po}$ decay. In EXO-200, $^{222}{\rm Rn}$ decays in the LXe outside of the active TPC volume cannot be tagged and give rise to a small background contribution.

The background model can further be used to test whether the pre-data taking radioassay of components, yield event rate estimations compatible with observation. The pre-data background rate predictions agreed, within the estimated uncertainties, with the rates derived from the final fit to the low-background data [12], thus indicating that the radioassay data has predictive power when coupled with an appropriate Monte Carlo model. It is interesting to note that the EXO-200 predictions made before data taking match as well [12]. A non-trivial conclusion follows from this observation. The event rates derived from the radioassay results assume Th and U decay chain equilibrium, while the data-driven analysis does not, thus validating the equilibrium assumption. Therefore, the methods employed during the planning and construction of EXO-200 can be considered reliable and justify their use during the design and construction of nEXO.

III. NEXO DETECTOR CONCEPT

A conceptual sketch of nEXO is shown in Fig. 1, with the liquid xenon volume enclosed in several layers of active and passive shielding. The principal parameters and dimensions of the experiment are presented in Table I.

In this concept, the TPC consists of a single homogeneous volume of 4038 kg of LXe enriched to 90% in the candidate $0\nu\beta\beta$ nuclide ¹³⁶Xe. An electric field drifts electrons toward the top of the TPC. Electric-field shaping rings, connected in a chain by resistors, create a po-

tential gradient in the LXe to achieve a uniform drift field. A drift field of 400 V/cm, similar to that of EXO-200, is planned. Deviating from the EXO-200 design, no center cathode is planned in nEXO. This is done in order to remove radioactivity from the center of the TPC and thereby taking full advantage of the substantial LXe- γ -ray attenuation, an important analytical tool. Hence, the design results in a single Xe-volume, delimited by cathode (at negative high voltage) and anode (at ground potential). This comes at the expense of a larger drift length and higher drift voltage requirements for equal field strength when compared to a mid-cathode design. In addition, the cryogenic charge readout electronics is only located at the top of the TPC (and the passive cathode at the bottom), thus minimizing xenon convection in the bulk of the LXe.

The field cage shaping rings are envisaged to be made of high-purity copper. Each of the 61 rings weighs 1.2 kg and are vertically spaced 2 cm apart. The field rings are separated by 24 1-cm high cylindrical sapphire vertical spacers (3.17 mm radial thickness) spread evenly along the ring circumference. The entire structure including the cathode and anode is held under compression by spring-tensioned sapphire rods with 1.59 mm radius that run the full length of the field cage, passing through holes in the rings and each of the spacers.

Several concepts are being investigated for the design and fabrication of the TPC cathode. For the purposes of the sensitivity calculations, the cathode is assumed to be a 0.25 mm thin copper disk held between two halves of an enlarged copper ring. The cathode sits 30 mm above the bottom of the TPC vessel.

Electrostatic simulations using COMSOL [24] were used to estimate the uniformity of the electric field in the drift volume. Near the edge of the field cage, distortions of the electric field lines prevent full charge collection for events within ~ 5 mm radial distance from the rings, radially defining the boundary of the fiducial volume. Electrostatic simulations are also used to position the HV components in a way such that the maximum electric field does not exceed a surface field of $50 {\rm kV/cm}$. This value was derived from COMSOL simulations of EXO-200 under high-voltage configuration that provided stable operating conditions.

An array of UV-sensitive silicon photomultipliers (SiPMs) detects scintillation light from particle interactions in LXe. The SiPMs are arranged in a "barrel" configuration on the mantle of the cylinder inside the TPC vessel and behind the field-shaping rings. There is no light collection at the top and bottom of the TPC volume, as the barrel region affords a better coverage and the top and bottom bases of the cylinder are occupied by the (opaque) charge collection tiles and cathode, respectively. Initial work on characterizing UV-sensitive SiPMs for use in nEXO has been published in [25].

The charge signal is envisioned to be read out on the anode by arrays of crossed strips, deposited on 10×10 cm² dielectric tiles [26]. The current choice for the chan-




FIG. 1. Engineering design rendering of the nEXO experiment concept, for concreteness drawn in the SNOLAB cryopit (left). Cross-section of the TPC (right).

nel pitch is 3 mm. Studies of the optimal value are ongoing. Compared to the wire readout used in EXO-200, the tile design simplifies construction and assembly. It further allows for the convenient placement of readout ASIC chips on the reverse of each tile. The signal induced by the drifting electrons on each strip is digitized and recorded independently.

The SiPMs and their associated read-out electronics are mounted on fused-silica backing structures supported by copper components. A similar arrangement is used for the charge read-out tiles and associated in-LXe front-end read-out electronics.

Flexible kapton cables, similar to those used in EXO-200, bring the ionization and scintillation signals out to the external data acquisition system. In nEXO, unlike EXO-200, the front end electronics and digitization are not external to the cryostat, but rather are in the LXe in close proximity to the TPC. In this design, the resulting relatively short cable runs for the analog signals will improve noise performance, and the reduced post-digitization cable plant reduces overall cable mass, at the cost of radiopurity constraints placed on the electronics. In this approach, the amount of cables does not scale with the size of the detector, owing to the digitization and multiplexing possible in this configuration.

The liquid xenon and TPC instrumentation are contained within a cylindrical vessel made of low-radioactivity copper. Initial engineering evaluations estimates the structural requirements of this vessel, including the mass of the copper, leading to a 3 mm-thick barrel with stiffened end-plates to manage static pressure loading.

Similar to EXO-200, the TPC vessel is conceived to be surrounded by a buffer of $\sim 33,000$ kg of HFE-7000, which is critical to the cryogenic setup as a thermal bath for the LXe. The HFE buffer also provides 76 cm

of shielding between the double-walled cryostat and the copper TPC vessel at their closest distance. The choice of the HFE-7000 thickness has been tuned to ensure backgrounds from the outer vessels and HFE-7000 itself are sub-dominant, as shown later.

The inner cryostat vessel, containing the HFE-7000, is modeled as spherical with a diameter of 338 cm. An outer vessel (diameter of 446 cm) provides the vacuum insulation required to maintain the inner cryostat at cryogenic temperature. The current concept employs carbon fiber with a titanium liner as construction material for the inner and outer vessels, in place of a more standard stainless steel solution. Carbon fiber provides better mechanical properties with potentially equal or better radiopurity. Unlike stainless steel, carbon fiber also allows for on-site fabrication in case large components cannot be brought into the underground facility. Support structures within each vessel are used to fix their relative positions. The outer vessel itself will be mounted from a top platform above a water tank.

A cylindrical stainless steel tank of 10 m height and 9 m diameter and filled with water is used as active muon veto and shields against natural radioactivity in the surrounding cavern walls. As a passive neutron shield, it reduces the neutron-induced background.

The experiment's location is still under evaluation and multiple options are being investigated. For concreteness, in the simulation the experiment is assumed to be located deep underground in the existing Cryopit at the Subdury Neutrino Observatory Laboratory (SNOLAB), near Sudbury, Ontario, Canada. With an overburden of 6010 meters water equivalent (m.w.e.) [27], this is a significant increase in depth over EXO-200 with its overburden of 1624^{+22}_{-21} m.w.e. [23], and provides a valuable reduction in all types of cosmic-ray induced backgrounds.

Particle	Process	Energy range
$\overline{\gamma}$	Livermore EM	< 1 GeV
e^-, e^+	Urbán Multiple Scattering	$<100~{\rm MeV}$
	Wentzel-VI Multiple Scattering	$>100~{\rm MeV}$
	Coulomb Single Scattering	$> 100~{ m MeV}$
e^-	Livermore Ionization	$<100~\rm keV$
	Livermore Bremsstrahlung	$< 1~{\rm GeV}$

TABLE II. Electromagnetic processes used in nEXO simulations. Energy ranges and additional particles that are not specified (muons, mesons, etc.) are governed by GEANT4.10.02 default physics.

IV. NEXO SIMULATIONS

A. Geometry and Event Generation

A Geant4-based application [28] is the primary tool used to simulate energy depositions in the detector. Table II describes the electromagnetic physics processes from Geant4.10.02 used in this simulation. Processes and particles not listed are left to the default Geant4 physics lists.

A GEANT4 geometry model implementation of the detector design described in section III was developed. The geometry uses standard Geant4 shapes to facilitate modifications allowing evaluation of design alternatives. While approximate geometries were used, care was taken to ensure all significant components are included, accounting for mass and materials properly. Visualizations of the simulated geometry are shown in Figure 2. The list of components is provided in Table III. Some detector components have not yet been included in the model. These are the high-voltage feed-through, the external support structures, and planned external calibration guide tubes. Due to their position and/or size, these missing components are not expected to contribute significantly to the overall background event rate and will be incorporated as the design becomes more detailed.

The GEANT4 Monte Carlo is used to generate and transport particles from radioactive decays. In order to save computing time, a subset of daughters of the $^{238}\mathrm{U}$ and $^{232}\mathrm{Th}$ chains are simulated independently and their resulting energy deposits subsequently merged with the appropriate branching ratios. Radionuclide selection is based on emission of γ radiation with energy >100 keV and with intensity > 1%. Table IV lists those nuclides individually simulated for the $^{238}\mathrm{U}$ and $^{232}\mathrm{Th}$ decay chains. Timing between the decays of daughter nuclides is not considered in the current reconstruction algorithm. Generation of $2\nu\beta\beta$ decays is performed using the algorithm in [29], validated in the EXO-200 analysis. It is biased to ensure a minimum of 10^5 simulated events with summed electrons energy above 2250 keV.

A FLUKA [30] model of nEXO has been developed for use in dedicated studies involving cosmogenic activation

and neutron interactions.

B. Detector Response

The experience of EXO-200 provides a basis for estimating nEXO's detection performance, in particular for reconstructing energy, position, and multiplicity of each event.

The output of the Geant4 simulation is reconstructed through software that applies detector effects from charge and light transport, and performs event analysis to extract the relevant event parameters.

First, in order to mimic the detector ability to identify distinct interaction sites, the GEANT4 energy deposits are aggregated by an algorithm that produces clusters of ~ 3 mm radius based on the relative position and energy of each deposit. This choice produces a SS fraction for background γ -ray events within $Q_{\beta\beta}\pm 1.7\cdot {\rm FHWM}$ that are about half ($\sim 10\%$) of that seen in EXO-200 ($\sim 20\%$). This reflects both our estimates of the projected hardware improvements (most notably the factor 3 reduction in charge channel pitch) as well as the sensitivity improvement obtained in EXO-200 Phase II using information about the SS cluster size [18]. A fiducial cut removes clusters that fall within 1.5 cm of the inner edges of the TPC field cage.

nEXO's energy resolution derives from extrapolating EXO-200's demonstrated performance. Accounting for the lower noise of nEXO's SiPM read-out, coupled with an expected light collection efficiency similar to EXO-200, nEXO's energy resolution is estimated as $\sigma/Q_{\beta\beta}=1\%$

The collection efficiency of the scintillation light is a key factor in determining the energy resolution in LXe TPCs. nEXO's GEANT4 model was used to propagate scintillation photons through the detector until they are absorbed in the SiPMs depletion region. The optical properties assumed for the detector surfaces are listed in Table \mathbf{V} . Considering that a SiPM light detection efficiency of 15% at 175 nm is achievable [25], simulations show that it is possible to obtain an average light collection efficiency of \sim 7%, comparable to that of EXO-200.

Due to the long drift length (~ 125 cm), an electron lifetime > 10 ms is deemed necessary so not to degrade the energy resolution. Electron lifetimes near this range have already been demonstrated [14, 15], and nEXO plans to limit electronegative impurities in the LXe arising from surface outgassing by utilizing substantially fewer plastic components than EXO-200 and thanks to a more favorable surface-to-volume ratio.

In the post-simulation reconstruction code, energy resolution is applied through convolution with a Gaussian distribution with a width obtained from a quadratic function analogous to that observed in EXO-200 [31] and coefficients scaled to achieve the expected nEXO resolution $\sigma/Q_{\beta\beta}=1\%$.

In addition to the event energy, the reconstruction also




FIG. 2. Visualization of the Geant4 simulation geometry. A cross-section of the components within the outer vessel are shown (left) with a close-up of the TPC (right). The underground laboratory walls and the large water shield surrounding the outer vessel are not shown but are included in the full Geant4 model geometry.

Component	Nuclides	Material	Mass or
	Simulated		Surface Area
Outer Cryostat	238 U, 232 Th, 40 K	Carbon Fiber	1774 kg
Inner Cryostat	238 U, 232 Th, 40 K	Carbon Fiber	338 kg
Inner Cryostat Liner	^{238}U , ^{232}Th	Titanium	$161.4~\mathrm{kg}$
HFE	^{238}U , ^{232}Th	HFE-7000	$32700~\mathrm{kg}$
TPC Vessel	^{238}U , ^{232}Th	Copper	$553.4~\mathrm{kg}$
Cathode	^{238}U , ^{232}Th	Copper	26.0 kg
Field Rings (FR)	^{238}U , ^{232}Th	Copper	$73.2~\mathrm{kg}$
FR Support Leg	238 U, 232 Th, 40 K	Sapphire	$0.94~\mathrm{kg}$
FR Support Spacer	238 U, 232 Th, 40 K	Sapphire	$2.21~\mathrm{kg}$
SiPM	238 U, 232 Th, 40 K	SiPM	$4.69~\mathrm{kg}$
SiPM Support	^{238}U , ^{232}Th	Copper	$136.4~\mathrm{kg}$
SiPM Module Backing	^{238}U , ^{232}Th	Quartz	$3.2~\mathrm{kg}$
SiPM Electronics	^{238}U , ^{232}Th	ASICs	$2.04~\mathrm{kg}$
SiPM Glue	^{238}U , ^{232}Th , ^{40}K	Epoxy	$0.12~\mathrm{kg}$
SiPM Cables	^{238}U , ^{232}Th	Kapton	$1 \times 10^4 \ \mathrm{cm}^2$
Charge Module Cables	^{238}U , ^{232}Th	Kapton	$1 \times 10^4 \ \mathrm{cm}^2$
Charge Module Electronics	^{238}U , ^{232}Th	ASICs	1.0 kg
Charge Module Glue	238 U, 232 Th, 40 K	Epoxy	$0.35~\mathrm{kg}$
Charge Module Support	^{238}U , ^{232}Th	Copper	$11.7~\mathrm{kg}$
Charge Module Backing	^{238}U , ^{232}Th	Quartz	$0.94~\mathrm{kg}$
TPC LXe Volume	$^{137}\mathrm{Xe},~^{222}\mathrm{Rn},~2\nu\beta\beta,~0\nu\beta\beta$	Xenon	$4038~\mathrm{kg}$
Outer LXe Volume	137 Xe, 222 Rn, $2\nu\beta\beta$, $0\nu\beta\beta$	Xenon	1071 kg

TABLE III. List of detector components included in the Geant4 model of nEXO with their material, nuclides simulated, and mass or surface area.

computes the event multiplicity from the number of clusters, thus classifying SS and MS events. The final output of the basic reconstruction consists of 2D histograms of energy vs standoff distance for each of the experiment's component and radionuclide of interest. Separate histogram for SS and MS events are created.

The reconstruction algorithm employed for this work is

simple and computationally inexpensive and was shown to be able to reproduce EXO-200 spectral shapes, providing confidence in the methodology while more advanced modeling is developed and validated.

A preliminary validation of the simple energy clustering algorithm was undertaken using a more sophisticated approach. Simulated energy deposits in the LXe were

Decay Chain	Nuclides generated
²³⁸ U	²³⁴ Pa, ²²⁶ Ra, ²¹⁴ Pb, ²¹⁴ Bi
$^{232}{ m Th}$	$^{228}{\rm Ac},~^{224}{\rm Ra},~^{212}{\rm Pb},~^{212}{\rm Bi},~^{208}{\rm Tl}$

TABLE IV. List of nuclides individually simulated for the $^{238}\mathrm{U}$ and $^{232}\mathrm{Th}$ decay chains.

Components	Properties	Value
Cathode	Reflectivity	80 %
Field Rings	Reflectivity	80 %
Anode (gold)	Refractive index	1.34 + 0.95i
SiO2	Refractive index	1.61 + 0i
Si	Refractive index	0.682 + 2.45i
LXe	Refractive index	1.66
LXe	Scattering length	$40~\mathrm{cm}$
LXe	Absorption length	20 m

TABLE V. Optical properties of surfaces used in simulating nEXO's collection efficiency for xenon scintillation light. Cathode and field rings are assumed to have a reflective coating. Values are given at a wavelength of 175 nm.

converted to electrons and photons using the Noble Element Simulation Technique (NEST) tool, designed to accurately model the scintillation and ionization yields in LXe and other noble-element media [32]. These photons and electrons were then propagated to collection, taking into account electron diffusion (electron diffusion coefficients were taken from [33]). Capture by electronegative impurities was neglected under the assumption of 10 ms electron lifetime and a maximum drift time of \sim ms at the nominal electric field. The induced signals on the charge tiles were computed using the Shockley-Ramo theorem [34, 35] and a COMSOL-generated weighting potential. Electronics sampling rate, noise, and threshold were applied to the waveforms which were then analyzed for signal amplitude, rise time, collection channel multiplicity, and position. A data analysis using multivariate classification techniques was performed on simulated samples of $0\nu\beta\beta$ (signal) and 2.5 MeV γ (background-like) events. The resulting SS/MS discrimination performance is consistent with that of the simple clustering algorithm described above.

Uncertainties due to systematic effects have not yet been investigated in detail. These systematics could arise for example from biases in the energy reconstruction or other calibration effects, and from detector response non-uniformities. Such effects were not significant in EXO-200 and are therefore not expected to significantly impact the sensitivity calculations.

V. BACKGROUNDS

A. Background Sources

Building a background model involves the pre-selection of radio-nuclides of interest. In deciding the composition of nEXO's background model, the following selection criteria were used:

- 1. The decay must release sufficient energy to interfere with the detection of the 136 Xe $0\nu\beta\beta$ mode.
- 2. The decaying nuclide must have sufficiently long half-life or be produced in steady-state in the detector. Otherwise, radioactive decay quickly diminishes the impact on the background of nuclides with a half-life time less than half a year.

A list of background sources that were considered during the assembly of nEXO's background model is provided in Table VI. These are discussed in detail in the remainder of this section. Components resulting in background event rates ≤ 0.02 SS events/(FWHM·y) in the inner 2000 kg LXe volume are not further considered. The choice of this volume will be discussed later in section VIIB.

Long-lived Radionuclides

The naturally occurring radioactivity of the 232 Th and 238 U nuclides fulfills the decay time selection criteria and, as a result, the decay chain daughters from each nuclide are included in the background model (as noted in Tab. IV). Of particular interest is the 238 U daughter 214 Bi which decay includes a γ -ray line at 2448 keV.

Long-lived nuclides such as ¹³⁷Cs, ⁶⁰Co, and ⁴⁰K are also considered. While they do not contribute to the $0\nu\beta\beta$ background due to energy and γ -ray multiplicity. they significantly affect the measurement of the $2\nu\beta\beta$ decay and are therefore systematically tracked as part of nEXO's materials analysis program. ⁴⁰K was explicitly included in the model as representative of low-energy spectral features. The probability that a $^{60}\mathrm{Co}$ decay result in a SS event with energy within $Q_{\beta\beta}\pm FWHM/2$ was estimated from Monte Carlo to be negligible ($< 2.3 \times 10^{-8}$ at 90% CL in the fiducial volume of 3740 kg). ⁶⁰Coinduced background is therefore negligible. The $2\nu\beta\beta$ decay of ¹³⁶Xe is included in the model. ²⁶Al is not currently included in the background model, but is planned for future study. Only γ and β decays from the nuclides above directly create background events in nEXO. Decays emitting only α particles are rejected with high efficiency using charge/light ratio analysis [36]. Secondary radionuclide production, e.g. through (α,n) reactions, is discussed below.

Background radioactivity was then further sub-divided into bulk and surface activities. The materials analysis program described in section VB tests all materials of interest for their bulk radioactivity content. It is assumed that surface activities can be mitigated by an appropriate surface treatment, cleaning, clean machining, and/or etching. This strategy was effective in EXO-200. The list of bulk radionuclides included in the Monte Carlo for each detector component in the nEXO background model is given in Table $\overline{\text{III}}$.

Background Source	
Long-lived radionuclides (γ - and β -emitters) in detector materials	In model
Th and U in water shield and lab rock	Negligible
Surface radioactivity	Negligible
α radioactivity	Negligible
Aboveground cosmogenic activation products	Negligible
Underground cosmogenic activation products in LXe	In model
Underground cosmogenic activation products in other detector materials	Negligible
136 Xe $2\nu\beta\beta$	In model
Activation products from (α,n) reactions	Negligible
Electron-neutrino elastic scattering	Negligible
Neutrino capture on ¹³⁶ Xe	Negligible
²²² Rn steady-state presence in LXe	In model
²²² Rn steady-state presence in water shield	Negligible

TABLE VI. List of background sources that were considered during the development of nEXO's background model and whether they were included in the sensitivity calculations. Details are provided in the text.

Several studies have demonstrated that a set of long-lived radionuclides from certain components of the experiment do not contribute significantly. For example, radiopurity levels of ²³⁸U and ²³²Th equal or better than 1 ppt have been achieved in water [37]. A dedicated simulation of these impurities in the water shield showed that the ²⁰⁸Tl and ²¹⁴Bi nuclides present in the decay chains contribute about 0.015 SS events/(FWHM·y) in the LXe volume inside the TPC field cage. The contribution of radioactivity in the shielding water was thus not considered in the background model.

Another source shown to be negligible is the natural radioactivity from the walls of the underground laboratory which was studied using a simplified experimental geometry. A layer of concrete and shotcrete covers SNO-LAB's cryopit rock walls. 226 Ra(238 U) and 232 Th in these materials at specific activities from [38] were found to contribute only 0.04 SS events/(FWHM·y) in the LXe volume inside the TPC field cage. Increasing the water shield radius by 1 meter, which e.g. still fits comfortably in the SNOLAB cryopit, would further reduce this background by a factor of ~ 100 .

Cosmogenically-created Radionuclides

Radionuclides with a half-life of less than 0.5 year were considered if they can be created by the interaction of the cosmic radiation with a material of interest. The estimation of this background class had two components: activation while materials are stored, handled, or machined above ground and the steady-state production underground. The former results in guidelines for the exposure management, the latter defines the requirements for the overburden.

Above-ground radio-nuclide production is important for all passive detector materials. In particular, the production of radio-nuclides in copper (e.g. ⁵⁶Co and ⁶⁰Co) was estimated and found to be acceptable with proper management of the cosmic ray exposure. Because the xenon will be continuously purified during de-

tector operation, long-lived spallation products created by the cosmic radiation while the xenon is above ground (e.g. ¹³⁷Cs) are not a concern. Xenon has no long-lived cosmogenically-produced isotope.

EXO-200 data was used to quantify a broad range of cosmogenic backgrounds [23] that would arise during underground operation. This was accomplished by testing GEANT4 and FLUKA Monte Carlo simulations against data, thus validating the models. These simulations were used, appropriately modified, to estimate cosmogenic backgrounds in nEXO, providing more confidence in the procedure. As a result, with sufficient overburden such as that available e.g. at SNOLAB, all cosmogenic backgrounds except 137 Xe are negligible. 137 Xe, which β -decays with a Q-value of 4173 keV, is therefore the only cosmogenic activity contained in the nEXO background model.

At SNOLAB, the steady-state production of cosmogenic 137 Xe in nEXO was estimated using FLUKA at 2.2×10^{-3} atoms/(kg·y). Siting nEXO at locations with similar overburden, like China Jinping Underground Laboratory [39], would also result in an acceptable cosmogenic nuclide production, even without active vetoing. The depth of Laboratori Nazionali del Gran Sasso (LNGS) [40], Italy, was found to be marginally acceptable and require the development of a more sophisticated active veto system. The Sanford Underground Research Facility (SURF), South Dakota, USA, [41, 42] at 4850' depth is adequate assuming a simple active veto scheme.

Neutrino-induced Backgrounds

Interactions of solar neutrinos in the detector are a potential source of background for $0\nu\beta\beta$ experiments, as discussed in [43–45].

Electron-neutrino elastic scattering $(\nu + e^- \rightarrow \nu + e^-)$ in the detector volume results in the emission of energetic electrons that can mimic the signature of a $0\nu\beta\beta$ event. Using the background rate for this reaction in ¹³⁶Xe from [45], ~0.02 SS events/(FWHM·y) are expected in

nEXO's inner 2000 kg of LXe. At this level this background is expected to be small compared to other backgrounds and thus we have chosen to set this as the level at which backgrounds are excluded from further investigation for the sensitivity calculation presented in this work.

The neutrino capture process via the charged-current reaction $\nu+^{136}{\rm Xe} \rightarrow e^-+^{136}{\rm Cs}$ also contributes background events due to (1) the prompt e^- combined with any γ -ray emitted from the $^{136}{\rm Cs}$ de-excitation, and (2) the delayed decay of $^{136}{\rm Cs}$ into $^{136}{\rm Ba}$ with a half-life of 13.16 days and Q=2548.2 keV.

The neutrino capture rate on ¹³⁶Xe is dominated by $^8\mathrm{B}$ solar neutrinos. The $^8\mathrm{B}$ neutrino capture rate is estimated to be $n_c=1.4\times10^{-3}$ captures/(kg·y) [44, 46, 47]. We conservatively assume that the prompt interactions following the capture process always result in an SS energy deposition. Only a small fraction of captures results in particles in the final state with energy $Q_{\beta\beta} \pm \text{FWHM}/2$. To first order, the energy distribution of the incoming neutrino and of the outgoing charged particles are similar. Therefore the fraction f_{ν} of ⁸B neutrinos that result in a $0\nu\beta\beta$ background can be estimated by multiplying the energy-differential average ⁸B neutrino flux by the projected FWHM energy resolution of nEXO at $Q_{\beta\beta}$, and then dividing by the total flux. The ⁸B neutrino flux average is computed from [48] and only for neutrinos with energy sufficient to transfer $E > (Q_{\beta\beta} - \text{FWHM}/2)$ to the emitted electron. The result of the calculation gives $f_{\nu} \sim 0.4\%$. The product of $n_c \cdot f_{\nu} \sim 0.01$ SS events/(FWHM·y·2000 kg) is the estimated background rate in nEXO from neutrino captures on ¹³⁶Xe. The presence of de-excitation γ -rays alongside the emitted electron results in a topological signature that would further reduce this background below the threshold for detailed consideration in the current sensitivity estimate.

The decay of $^{136}\mathrm{Cs}$ consists of a low energy electron and multiple concurrent γ -rays. Monte Carlo simulations show that this high multiplicity results in a probability of $< 2.3 \times 10^{-7}$ at 90% CL for $^{136}\mathrm{Cs}$ to produce a SS event with energy near $Q_{\beta\beta}$. Even assuming that $^{136}\mathrm{Cs}$ is not removed by the LXe purification system or does not freeze-out on metal surfaces, the decay of all $^{136}\mathrm{Cs}$ in the LXe would thus result in a negligible background rate in nEXO.

Radionuclides from (α,n) Reactions

Deposition of the α -unstable ²²²Rn daughter ²¹⁰Po can create background through (α,n) reactions with low-Z detector materials such as F, C, O, Al, and Si which are contained in nEXO's HFE-7000, sapphire, and quartz. The emitted neutrons can subsequently produce ¹³⁷Xe when capturing on ¹³⁶Xe.

A calculation was performed to determine the allowable exposure time of these materials to standard lab air (25 Bq/m3 222 Rn) before radon daughter plate-out

results in more than 0.01 events/(FWHM·y·3000 kg) of background. Neutron yields for the relevant (α,n) reactions were calculated from tabulated stopping power and cross-section data, and used as input into a FLUKA simulation to determine the position distribution and probability of neutron captures on 136 Xe in nEXO from neutrons generated on the surface of the relevant components. Capture events were found to be uniformly distributed in the LXe. The nEXO GEANT4 Monte Carlo provided the fraction of 137 Xe decays that result in a SS energy deposition within $Q_{\beta\beta}\pm {\rm FWHM}/2$. Measured radon-daughter deposition rates [49] were used. A constant 210 Po decay rate has been assumed, leading to an over estimate of the neutron production as the slow Pogrowth is not accounted for.

Of the surfaces considered, those in contact with the HFE-7000 would be subject to the most restrictive exposure time constraint of 7.5 y/m². Therefore, the steady-state production of $^{137}\mathrm{Xe}$ from $\alpha\text{-induced}$ neutrons can be neglected under the assumption that proper surface treatment and handling will be performed during construction.

^{222}Rn

Contributions to the background rate from the $^{222}\mathrm{Rn}$ daughter $^{214}\mathrm{Bi}$ must be considered because $^{214}\mathrm{Bi}$ emits a γ -ray with an energy only 10 keV lower than the $Q_{\beta\beta}$ value. As a result, any process that contributes a steady-state population of $^{222}\mathrm{Rn}$ inside the LXe volume is important. For the purposes of estimating the sensitivity, it is assumed that nEXO will have $600^{-222}\mathrm{Rn}$ atoms continuously present in the LXe, a factor of 3 higher than observed in EXO-200. This factor is based on an estimate of the expected inner surface area of the xenon recirculation system in nEXO relative to EXO-200.

Events from the ²²²Rn decay chain can be tagged using a Bi-Po veto which identifies time- and space-correlated β and α decays. An equivalent efficiency as that achieved by EXO-200 was assumed for nEXO to reject Bi-Po events from ²¹⁴Bi decaying directly in the LXe volume inside the TPC field cage. Tagging or vetoing of ²¹⁴Bi decays in the LXe outside the TPC field cage may be possible in nEXO by exploiting the light collected by the SiPMs on the barrel (not possible in EXO-200). The ability to identify ²¹⁴Bi decays from ²²²Rn daughters that have drifted on to the cathode is the subject of ongoing studies, including special cathode designs and analysis techniques. The background model presented in this work combines ²¹⁴Bi in the region outside the TPC field cage and on the cathode into one term, and assumes a tagging efficiency of $\sim 40\%$ for these decays.

 222 Rn can dissolve into the water of the water shield, producing a background from γ -rays penetrating in the TPC. Assuming a Rn concentration level of 9×10^{-9} Bq/kg total from all components exposed to water (steel tank, pumps, other materials, etc.), Monte Carlo simula-

tions show the background contribution to be negligible. This concentration requirement is satisfied if the wetted steel has no more than 10 ppb U, expected to be easily achievable.

B. Detector Component Materials and Assays

Radioassay of detector materials is a central aspect of demonstrating feasibility and from which to base sensitivity projections on realistic assumptions. This activity is intimately connected with the Monte Carlo and engineering efforts, enabling the preliminary detector engineering to be performed with appropriate low activity materials. This is essential for the iterative development of a compelling and realistic experiment concept. nEXO's approach follows the example of the successful EXO-200 materials certification and background estimation efforts [21, 22].

This effort is being conducted at multiple collaborating nEXO labs worldwide. In addition, commercial services are utilized whenever appropriate. The following assay techniques have been utilized (benchmark sensitivities given in square brackets, for Th/U in techniques 1-4):

- 1. Above ground and underground low background γ -ray spectrometry. Purpose designed shielded Ge detectors are utilized. [routine: 200/35 ppt, 2.3/1.2 ppt achieved with very large samples]
- 2. Inductively coupled plasma mass spectrometry (ICPMS). [routine: 1/1 ppt, 0.008/0.01 ppt achieved with pre-concentration][50]
- 3. Glow discharge plasma mass spectroscopy (GDMS). [10/10 ppt]
- 4. Neutron activation analysis (NAA). [routine: 1/1 ppt, 0.02/0.02 ppt achieved with sample preconcentration]
- 5. Radon out-gassing via electrostatically-boosted solid state detection or liquid scintillation counting $[3 \text{ atoms}/(\text{m}^2 \text{ d})]$
- 6. Low background $\alpha\text{-counting}$ using Si solid state detector [210Po: 30 mBq/m²]

These methods complement each other. ICPMS and NAA offer the best sensitivity at the levels required for the innermost and most demanding detector components. However, converting the concentrations of nuclides at the head of the decay chains, determined by these methods, into background rates requires assumptions regarding the chain equilibrium. Assuming secular equilibrium is realized, these techniques can only estimate, rather than rigorously predict, the expected background rates. γ spectroscopy with Ge detectors directly determines the background relevant Th and U-chain members $^{208}{\rm Tl}$ and

 214 Bi. γ -ray spectroscopy is further used to probe for short lived activities (cosmogenic or man-made). Radon counting directly probes backgrounds from this nuclide.

Table VII lists the detector materials and activities entering into the current background estimate. Except for three cited entries, Table VII presents new nEXO measurements of these materials, not previously published elsewhere.

The nEXO material assay data are recorded and stored in an online database. The data catalog systematically keeps track of measurement values and uncertainties to enable the computation of a total background rate, accounting for errors. For convenience Table VII lists 90% CL limits whenever the value is consistent with zero at 90% CL, assuming the errors follow the normal distribution. The limit conversion uses the "flip-flop" method [51] to avoid inflating the sensitivity for un-physical negative concentrations. For measurements near the limit of sensitivity, which is often the case for nEXO samples, seemingly un-physical results are encountered and dealt with in a consistent fashion, as described above.

VI. SENSITIVITY AND DISCOVERY POTENTIAL METHODOLOGY

The sensitivity and discovery potential of nEXO are determined by finding the confidence interval of the $0\nu\beta\beta$ rate of an ensemble of simulated trial experiments, here called "toys". The confidence interval of a toy experiment is determined using a profile likelihood method. In this method, each possible signal rate is treated as a single hypothesis to be tested against the data. Each hypothesis is fit against the data and assigned a likelihood-based test statistic, λ . The confidence interval is the set of signal rate hypotheses with λ values below a threshold determined to produce the desired degree of confidence.

To calculate sensitivity, an ensemble of toys is generated assuming zero $0\nu\beta\beta$ events, and the upper limit of the 90% confidence interval is determined for each toy. The sensitivity is the median upper limit of this ensemble. The discovery potential is determined by finding the mean $0\nu\beta\beta$ rate for which 50% of toys exclude the null hypothesis from the 99.7% confidence interval.

This method has many similarities to that used to calculate EXO-200's experimental limit, with a significant difference imposed by the improvements in nEXO. The EXO-200 analysis verified that EXO-200's data falls under the conditions of validity of Wilks's theorem [53], and therefore took advantage of the consequent statistical simplification: a single threshold value of λ defines the 90% confidence interval, referred to as λ_c .

nEXO's data will include fewer background events than EXO-200, thus precluding the use of Wilks's theorem which provides an accurate approximation in the limit of large event rates. As a result, nEXO must directly calculate a separate value for the threshold λ_c at each hypothesis to include or exclude a given fit result

Material	Supplier	Method	K	Th	U	$^{60}\mathrm{Co}$
			[ppb]	[ppt]	\mathbf{U} [ppt]	$[\mu \mathbf{Bq/kg}]$
Copper	Aurubis	ICPMS/Ge/GDMS	< 0.7	0.13 ± 0.06	0.26 ± 0.01	< 3.2
Sapphire	GTAT	NAA	9.5 ± 2.0	6.0 ± 1.0	< 8.9	-
Quartz	Heraeus	NAA	$0.55{\pm}0.04$	< 0.23	< 1.5	-
SiPM	FBK	ICPMS/NAA	< 8.7	$0.45{\pm}0.12$	$0.86{\pm}0.05$	-
$Epoxy^*$	Epoxies Etc.	NAA	< 20	<23	<44	-
Kapton*	Nippon Steel Cables	ICPMS	-	$<2.3 \text{ pg/cm}^2$	$4.7\pm0.7~{\rm pg/cm^2}$	-
HFE^*	3M HFE-7000	NAA	< 0.6	< 0.015	< 0.015	-
Carbon Fiber	Mitsubishi Grafil	Ge	550 ± 51	58 ± 19	19 ± 8	-
ASICs	BNL	ICPMS	-	25.7 ± 0.7	13.2 ± 0.1	
Titanium	TIMET	Ge	< 3.3	57 ± 5	< 7.3	-
Water	SNOLAB	Assumed	<1000	<1	<1	-

TABLE VII. Materials, analysis method and radioactivity concentrations entering the nEXO background model. Data for entries marked with a * were taken from the EXO-200 materials certification program. Data for titanium are from Table VI of Ref. [52]. Limits are stated at 90% CL and were computed using the "flip-flop" method [51].

from the confidence interval. The method used here relies on the techniques described in [51] which shows how to set confidence intervals correctly according to the frequentist definition while operating in limits where statistical simplifications cannot be relied upon.

There are two phases to calculating the confidence intervals for nEXO simulated data. In the first phase, the distribution of the test statistic λ is calculated for each signal hypothesis μ . This determines λ_c , the critical value to include a given hypothesis in an experiment's confidence interval. The distributions are calculated for a specific experimental duration (the "live time") and background expectation, and can be used to find the limits for any experiment with the same live time and backgrounds. In the second phase, an ensemble of toy experiments is generated and the confidence interval is calculated for each experiment using the previously determined λ_c . The median upper limit of the confidence intervals of and ensemble generated under the null hypothesis is nEXO's sensitivity.

A. Generating Toy Experiments

Toy datasets are generated by randomly sampling the probability distributions functions (PDFs), $S_j^{\rm SS,MS}$, describing the energy-standoff distribution in the detector arising from each background component j, with SS and MS PDFs considered separately. When evaluating $\lambda_c(\mu)$ for $\mu > 0$, the toy datasets also sample the $0\nu\beta\beta$ PDF.

These PDFs are created from the distribution in energy-standoff space of simulated backgrounds generated by nEXO's GEANT4 MC and reconstruction. Following the EXO-200 analysis, an energy threshold of 800 keV is used.

The overall normalization n of each component j's PDF was set using the formula:

$$n_j^{\rm SS,MS} = M_j \cdot \varepsilon_j^{\rm SS,MS} \cdot A_j T$$
 (3)

where M is either the mass or the surface area of the

detector component (whichever is relevant), ε is the hit efficiency, A is the specific activity for the nuclide, and T is the observation time. Except for T, all entries in (3) are component-specific.

The hit efficiency $\varepsilon^{\rm SS,MS}$ is the probability that a decay in a specific detector component will produce an event of given multiplicity within the energy and standoff selection region. $\varepsilon^{\rm SS,MS}$ is obtained from nEXO's Geant4 MC, as described in section IVB. The number of MC events generated was chosen to keep the statistical uncertainty in the hit efficiency in the inner LXe volume and near the $0\nu\beta\beta$ Q-value within $\sim 20\%$ for all significant background contributors.

Since their true values are unknown, the values for the activities A_j are sampled for each toy experiment from Gaussian distributions truncated at zero and with parameters given by the measured central value and uncertainty from the radioassay measurements in Table VII. One random draw is performed per material, such that the value of A_j is the same for all background components made of the same material. For radioassays that returned only upper limits, the Gaussian distribution is assumed as centered at zero with the appropriate uncertainty to match the limit. This method introduces a Bayesian element to what is otherwise a frequentist limit-setting methodology by describing the uncertainties in isotope activities with prior probability distributions.

Equation (3) and the $S_j^{\rm SS,MS}$ are combined to produce a total background spectrum PDF in energy-standoff space. This PDF is then randomly sampled to produce a toy dataset, represented by two histograms for the SS and MS events.

Evaluating the $\lambda_c(\mu)$ curve requires $\sim 100,000$ toy datasets, at varying values of μ . Once the curve is known, 10,000 toys with $\mu=0$ are used to estimate the sensitivity.

B. Fitting Toy Data

Each toy dataset is fit by minimizing the negative log-likelihood (NLL, \mathcal{L}) constructed from the MC-generated PDFs of each component:

$$\mathcal{L}_{\text{nEXO}} = \mathcal{L}_{\text{SS}} + \mathcal{L}_{\text{MS}} - \ln(G_{\text{const}}) \tag{4}$$

where $\mathcal{L}_{\mathrm{SS(MS)}}$ is the binned NLL built from the toy SS (MS) data compared to the corresponding PDFs $S_j^{\mathrm{SS,MS}}$ generated by the nEXO MC for each background j (and the $0\nu\beta\beta$ signal). The definition of the logarithmic likelihood function closely follows that outlined in section 6.2 of [15]. The fit parameters are the expected number of counts in each component, n_j^{SS+MS} (total, both SS and MS) and the fraction of SS events in that component f_j^{SS} . These parameters are fit, rather than being fixed, to accommodate the uncertainty the final nEXO experiment will have about background intensities and SS/MS discrimination.

 $G_{\rm const}$ is a multivariate Gaussian function constraining some fit parameters. The SS fractions $f_{\rm SS}^j$ for all components are constrained to be within 5.9% of the mean obtained by the MC simulations, as per [15]. The background rate from $^{222}{\rm Rn}$ in the LXe outside of the TPC region is constrained to be within 10% of the expectation rate, as this will be well known during the experiment by studying tagged $^{222}{\rm Rn}$ in the TPC volume. The normalization terms n_j^{SS+MS} are unconstrained. The covariance matrix is diagonal in this study, as systematics causing correlation between data bins have not yet been taken into account.

The NLL fit is implemented using ROOFIT [54] and MINUIT [55].

C. Calculating the Test Statistic Distribution

The NLL ratio test statistic is calculated as

$$\lambda(\mu) = 2\left(\mathcal{L}_{\mu} - \mathcal{L}_{\mu_{\text{best}}}\right) \tag{5}$$

where \mathcal{L}_{μ} is the log-likelihood fixing the signal expectation to μ and $\mathcal{L}_{\mu_{\text{best}}}$ is the log-likelihood letting the signal parameter assume its best-fit value μ_{best} .

Instead of relying on Wilks's theorem, the NLL ratio threshold $\lambda_c(\mu)$ is explicitly computed at all values of μ covered in this study.

Following the approach suggested in [51], the $\lambda_c(\mu)$ curve is obtained in a frequentist manner via MC generation of the distribution of the test statistic under each hypothesis. Over a range of hypotheses μ , an ensemble of toy experiments is generated with a number of signal counts randomly drawn from the expectation μ . The value of $\lambda(\mu)$ for each of these experiments is computed and the 90th percentile of the resulting distribution of $\lambda(\mu)$ defines the critical value $\lambda_c(\mu)$ for the 90% confidence interval used for sensitivity. The 99.7th percentile




FIG. 3. Distribution of μ_{90} , the upper limit on the signal counts under the null hypothesis, obtained for several background realizations (toy experiments) at 10 years livetime.

similarly defines $\lambda_c(\mu)$ for the 99.7% confidence interval used for the discovery potential.

Calculating $\lambda_c(\mu)$ requires generating and fitting an ensemble of many toys under a range of values for μ . In order to reduce computing time, the calculation is performed at several discrete points which are then fit with a third-order spline. This produces a smooth curve that interpolates between the calculated points and reduces the impact of the statistical uncertainty of the calculation of a quantile on a finite distribution.

The $\lambda_c(\mu)$ curve is obtained under a specified live time and expected distribution of backgrounds. Changing either of those assumptions requires the calculation of a new curve.

D. Calculating Sensitivity and Discovery Potential

For any single toy data set, a given value of μ is included in the set of hypotheses that make up the confidence interval C if $\lambda(\mu) < \lambda_c(\mu)$. A bisection algorithm is used to minimize the number of $\lambda(\mu)$ points that must be calculated for each toy experiment to determine μ_{90} , the crossing point (or the greater of two crossing points, if two exist) between $\lambda_c(\mu)$ and $\lambda(\mu)$. This approach was validated by comparing the results obtained in the high-statistics regime, where Wilks's theorem holds, against those from MINUIT.

nEXO's sensitivity at a given background and live time is extracted as the median of the distribution of the upper limit μ_{90} from an ensemble of toy experiments generated with the null hypothesis $\mu=0$ and under those livetime and background assumptions. An example of the distribution of μ_{90} is shown in Fig. 3. The $0\nu\beta\beta$ half-life sensitivity is then inferred from the median μ_{90} , the number of 136 Xe nuclei and the experiment's live time.

In addition to the sensitivity, the median discovery potential at 3-sigma is also calculated. An experiment is

a discovery if the 99.7% confidence interval, calculated as described above, does not include the null hypothesis $\mu=0$. The median discovery potential is the $0\nu\beta\beta$ half life that produces discovery experiments 50% of the time. Determining the discovery potential entails a search over $0\nu\beta\beta$ rates to find which rate produces 50% discoveries.

VII. SENSITIVITY AND DISCOVERY POTENTIAL TO $0\nu\beta\beta$

A. Simulated Spectra and Background Budget

Three parameters –energy, standoff distance, and event type (SS or MS)– are used to characterize signal and background events.

As an example of this multi-dimensional analysis, the SS and MS spectra from one of the simulated toy experiments are given in Fig. 4. Best fit results for all radionuclides (arranged by component groups) are shown. Overall, the energy spectra are dominated by $2\nu\beta\beta$ events, while the tail of the ²¹⁴Bi photoelectric peak is the largest background contributor near the $0\nu\beta\beta$ Q-value. As a function of standoff distance, the distribution of external radioactivity drops rapidly and is markedly different than the distribution of $0\nu\beta\beta$, $2\nu\beta\beta$, and ¹³⁷Xe events which are uniform throughout the LXe volume. This behavior adds resolving power other than energy to the analysis, improving the ability to distinguish a $0\nu\beta\beta$ signal from background.

To highlight the backgrounds of greatest concern, the standoff distribution is shown in Fig. 5 with a cut selecting the $\pm \text{FWHM}/2$ energy region around $Q_{\beta\beta}$.

In the central region of the detector, external gamma backgrounds are reduced by several orders of magnitude (Fig. 6). Given the size of nEXO and the absence of any material other than LXe within the TPC volume, 2.5 MeV gamma-rays have to traverse more than 7 attenuation lengths, and likely scatter multiple times, before reaching the center of the LXe volume.

The diagnostic power of nEXO's multi-parameter approach can be further appreciated by looking at Fig. 7. While the energy resolution alone marginally resolves a $0\nu\beta\beta$ -peak from γ -peaks caused by external radioactivity, the standoff distance variable provides the additional resolving power in combination with the event-type variable (SS/MS). The large body of xenon is not simply used as a passive shield but actively measures external backgrounds and internal double beta decays simultaneously. The outer volumes effectively quantify external backgrounds, while the inner volumes determine the $\beta\beta$ -signal. This combination of variables adds confidence in case of a discovery.

The count rate as a function of the fiducial mass is shown in Fig. 8 for events in an energy window $\pm \text{FWHM}/2$ around $Q_{\beta\beta}$. Shown is the median and 95% band of the distribution resulting from the random draw of activities described in section VI A. Clearly, a large ho-

mogeneous detector like nEXO cannot be characterized by a single background index value. Instead, its background rate is a position-dependent function. While for specific and circumscribed purposes it may be convenient to think in terms of a single background rate in a region of energy, one should always be aware that this point of view is not generally appropriate here. However, as a reference, nEXO is predicted to achieve a background rate of 2.9×10^{-4} cts/(FWHM·kg·y) in the inner 2000 kg of LXe. This choice of mass value will become clear in the next section.

Fig. 9 visualizes the contribution of different background components and their uncertainties. This figure shows the measured activities in Table VII multiplied by the SS hit efficiency for events with energy within $Q_{\beta\beta}\pm {\rm FWHM}/2$ and within the inner 2000 kg of LXe. Contributions to the background budget are grouped by material, nuclide, and component. Contributions for which a measured radioassay exists are considered separately from those for which only an upper limit is available

 γ -ray interactions from the ²³⁸U decay chain constitute more than 70% of nEXO's background in the inner 2000 kg. A fraction of this component arises from materials for which only upper limits are currently available. Hence nEXO's expected background may fall as these radioassays are replaced by more precise measurements or higher purity materials are selected for use in the nEXO design.

Improvements in the data analysis are also expected to reduce the background arising from $^{137}\mathrm{Xe}$. This is important because, as shown in Fig. 5, this background is uniformly distributed in the detector volume. At a sufficiently deep location, a straightforward active muon veto could efficiently reduce the $^{137}\mathrm{Xe}$ with acceptable loss in livetime. As a conservative measure, no muon-based vetoing has been assumed in the analysis presented here.

The breakdown by component in Fig. 9 shows that TPC elements dominate the background due to their vicinity to the central LXe region, while massive but distant components such as the cryostat vessels are subdominant. By material, the largest contribution arises from radio-impurities in the copper, primarily in the TPC vessel which is the largest-mass component near the LXe. Cables and field rings (and their associated support equipment) are the next largest components. Overall, background counts are rather evenly distributed across various TPC internal components. This is indicative of a well-balanced experimental design.

B. Sensitivity Results

nEXO's size and extremely low background levels, coupled with the fit analysis which exploits the multiparameter event signature provided by the TPC technique, result in a dramatic improvement in sensitivity




FIG. 4. Result of the NLL fit on a representative nEXO toy dataset generated assuming a $0\nu\beta\beta$ signal corresponding to a half-life of 5.7×10^{27} y and 10 years of detector live time. The top plots are the energy distribution histograms while the bottom plots are the standoff distances; left (right) spectra are for SS (MS) events.




FIG. 5. Standoff distribution for the fit results from a representative toy MC dataset with 10 years live time. Only SS events with energy within $Q_{\beta\beta}\pm {\rm FWHM}/2$ are included. The $0\nu\beta\beta$ signal corresponds to a half-life of $5.7\times10^{27}{\rm y}$.




FIG. 6. Distribution of SS counts for a representative toy MC experiment as a function of energy and standoff distance for the 238 U (left) and 232 Th (right) background arising from all TPC internal components.




FIG. 7. Energy spectra for SS and MS events as a function of the LXe mass. Spectra are evaluated for a detector live time of 10 years. The $0\nu\beta\beta$ signal corresponds to a half-life of 5.7×10^{27} years.

compared to EXO-200 achievements. nEXO's median sensitivity on the $0\nu\beta\beta$ half-life for $^{136}\mathrm{Xe}$ at 90% C.L. is shown in Fig. 10 as a function of the experiment's live time. After 10 years of data collection, the median 90% C.L. sensitivity reaches 9.2×10^{27} years. A 3σ discovery potential of 5.7×10^{27} years is predicted for the same live time.

The two-dimensional fit of energy and standoff distance allows nEXO to maximize its sensitivity by employing the largest possible fiducial volume, in contrast

to a counting analysis which reaches maximum sensitivity only with a substantial fiducial volume cut. This is shown in Fig. 11. Indeed, the full two-dimensional analysis shows an improvement of ${\sim}50\%$ over a counting-style experiment. Fig. 11 also motivates the earlier choice of presenting the background rate for the innermost 2000 kg of LXe where ${\sim}90\%$ of the full sensitivity is achieved and a counting-style rate analysis reaches its maximal sensitivity.

The results presented are based on a robust estimation




FIG. 8. Median background as a function of the LXe fiducial mass derived from 10^4 toy-MC simulations with detector live time of 10 years. The band corresponds to the 95% confidence belt of the distribution of background counts at each fiducial mass value.

of the backgrounds and realistic detector performance, extrapolated from EXO-200 and supported by nEXO-specific modeling results. We note that these results do not involve any extrapolation of materials radiopurity beyond what has been already measured. As the R&D continues, it is possible that better performance might be achieved e.g. through improved material selection and engineering, improved analysis techniques, or hardware breakthroughs.

Traditionally, the analysis of energy spectra alone has been the workhorse of $0\nu\beta\beta$ searches, thus favoring calorimetric experiments with very high energy resolution. Over time, all $0\nu\beta\beta$ searches have started to introduce multiple parameters to measure and reject backgrounds (see e.g. [56–58]). By including standoff distance and event type (SS/MS), EXO-200 was able to provide outstanding physics results in spite of a somewhat limited energy resolution. nEXO's larger mass enhances the utility of these additional variables in the multi-parameter analysis, further lessening the reliance on energy resolution. The homogeneous nature of the detector permits to take full advantage of this multi-parameter approach.

The impact of the energy resolution on nEXO's sensitivity is shown in Fig. 12. The shallow slope of this curve is understood by considering the role of the photoelectric peak from $^{214}{\rm Bi}$ background, which falls only 10 keV away from the $^{136}{\rm Xe}$ $0\nu\beta\beta$ Q-value. In the range of energy resolutions considered here, only a small fraction of SS $^{214}{\rm Bi}$ backgrounds lies more than $\pm {\rm FWHM}/2$ away from $Q_{\beta\beta}$. Even at an energy resolution of 0.35%, 50% of the $^{214}{\rm Bi}$ SS background falls within $Q_{\beta\beta}\pm {\rm FWHM}/2$. For this reason, the half-life sensitivity does not significantly change with the energy resolution. On the other hand, the sub-dominant contribution arising from the fraction of SS $^{208}{\rm Tl}$ decays that enter the same energy window is only 2.6×10^{-5} at 1% resolution. This fraction increases

rapidly as the resolution worsens, becoming 2.8×10^{-2} at $\sigma/Q_{\beta\beta} \sim 1.5\%$.

The standoff and event type parameters in nEXO's multi-parameter analysis have no discriminating power against the unavoidable $2\nu\beta\beta$ background. As a result, energy resolution is the only proven method to suppress this background. Figure 13 shows the calculated $2\nu\beta\beta$ event rate in nEXO as a function of the energy resolution (assumed Gaussian). At nEXO's design energy resolution, the contribution of $2\nu\beta\beta$ decays at $Q_{\beta\beta}\pm FWHM/2$ amounts to only 0.34 counts over 10 years of data taking in the entire LXe volume, and is therefore negligible. This is also due to the fact that the $2\nu\beta\beta$ half-life for 136 Xe has been found to be smaller than that of all other common $0\nu\beta\beta$ candidates [59].

These results support nEXO's target energy resolution of $\sigma/Q_{\beta\beta}=1\%$ and suggest that further improvements, while beneficial, are not critical to achieving a compelling sensitivity.

C. Sensitivity Variation Studies

Ongoing efforts focus on reducing the SS backgrounds through advancement in material screening and selection, optimization of the detector components (e.g. mass and location), and improved analysis. A parametric study was performed to evaluate the improvement in $0\nu\beta\beta$ sensitivity as a function of the total background. All materials activities from table VII were uniformly scaled down by progressively larger fraction, with the exception of the $2\nu\beta\beta$ component which was held constant. New toy data sets were generated and then fit to obtain a median sensitivity estimate for different background scenarios. The resulting curve is shown in Fig. 14, assuming 10 years of data taking. The $0\nu\beta\beta$ sensitivity increases by a factor 4 as the background rate is lowered by two orders of magnitude. The point labeled "baseline" refers to the case described in this paper, while "aggressive" refers to a case in which still plausible improvements are made.

It is interesting to observe that for nEXO, the common approximation that sensitivity $T_{1/2}^{0\nu}$ scales with background B as $1/\sqrt{B}$ is not valid. Indeed, fitting the calculated sensitivity points in Fig. 14 with a power law results in

$$T_{1/2}^{0\nu} \propto \frac{1}{B^{0.35}}$$

This finding is significant. First, it underlines the importance of using experiment-specific techniques to estimate sensitivities. Second, it shows that nEXO is less sensitive to background fluctuations than what might be inferred from a simple $1/\sqrt{B}$ scaling.

Hypothetically, the detection of a discrete energy deposit at $Q_{\beta\beta}$, due to some yet unknown decay, could lead to an unjustified claim of discovery of $0\nu\beta\beta$ -decay. Clearly, having multiple competitive $\beta\beta$ -experiments world-wide, based on different decaying nuclides, would




FIG. 9. Histograms of the SS background contributions by nuclide (top left), material (top right), and detector component (bottom). for nEXO with energy within $Q_{\beta\beta}\pm {\rm FWHM/2}$ and in the inner 2000 kg. The arrows indicate 90% C.L. upper limits while the circles indicate measured values with 1σ uncertainties. Systematic uncertainties and contributions smaller than 5×10^{-7} cts/(FWHM·kg·y) are not shown.

provide a robust defense against this problem. However, due to its multi-parameter measurement capability nEXO is robust against such an unknown background. Discrete energy deposits are due to α -particles, conversion electrons or γ -rays and can arise from decays internal or external to the LXe. An α -decay could be identified by its characteristic scintillation to ionization ratio and is therefore not problematic for nEXO. The case of an unknown external γ -ray source can be studied with the existing simulations. Such background would follow the

same distribution in standoff and SS/MS as other external backgrounds. If an unknown decay were strong enough to produce as many SS events in the inner 3000 kg as a 3σ discovery at a half life of 5.7×10^{27} years, this decay would produce 271 counts in the MS outer volume, enough to rule out the expected background model at p<0.00001. Due to their complexity, the other cases of unknown backgrounds from conversion electron or γ -rays within the LXe will be the subject of future studies.




FIG. 10. nEXO median sensitivity at 90% CL and 3σ discovery potential as a function of the experiment livetime.




FIG. 11. nEXO exclusion sensitivity at 90% C.L. as a function of fiducial LXe volume. The blue points (upper curve) are obtained from the full 2D energy-standoff fit, while the black points (lower curve) are the result of a pure counting experiment of events with energy in $Q_{\beta\beta}\pm {\rm FWHM}/2$. Both analyses are performed using the method of [51].

The case of an experiment entirely dominated by $2\nu\beta\beta$ background was considered as one limit to the possible sensitivity of nEXO. Techniques have been proposed that could potentially make this possibility a reality [60, 61]. This is an area of intense R&D and, while challenges are still to be overcome, nEXO's current design leaves open the possibility of deploying upgrades at later stages of




FIG. 12. nEXO median exclusion sensitivity at 90% CL computed for different assumptions of the experiment's energy resolution.

the experiment's lifetime. Sensitivity and discovery potential to $0\nu\beta\beta$ under a $2\nu\beta\beta$ -only background scenario are provided in Fig. 15, in analogy with Fig. 10.

VIII. CONCLUSIONS

nEXO's sensitivity reach is rooted in the success and experience gained from its predecessor EXO-200 and in




FIG. 13. Calculated $^{136}\mathrm{Xe}~2\nu\beta\beta$ SS events falling within \pm FWHM/2 of the $^{136}\mathrm{Xe}$ Q-value as a function of the energy resolution (assumed Gaussian). The expected and measured energy resolution of nEXO and EXO-200 respectively are shown for reference.




FIG. 14. Sensitivity (blue circles) to the $0\nu\beta\beta$ half-life of a nEXO-like experiment as a function of total background in $Q_{\beta\beta}\pm {\rm FWHM}/2$ in the inner 2000 kg. All components of nEXO's background model except for the $2\nu\beta\beta$ term are scaled to generate this curve. The red curve is the result of fitting the computed values with $T_{1/2}^{0\nu} \propto B^x$, giving x=-0.35.

the advantages provided by a large homogeneous TPC with good energy resolution, position reconstruction, and ability to identify particle type.

Making conservative assumptions on the detector and analysis performance, and using only measured radioassay inputs to build the background model, we predict that nEXO will reach a 3σ discovery potential of 5.7×10^{27} years for the $^{136}\mathrm{Xe}$ $0\nu\beta\beta$ half-life. We further estimate its 90% CL exclusion sensitivity to reach 9.2×10^{27} years. Under aggressive but not unrealistic assumptions, nEXO might reach well beyond a sensitivity of 10^{28} years.

The sensitivity to the $0\nu\beta\beta$ half-life of 136 Xe can be




FIG. 15. Median exclusion sensitivity at 90% C.L. and 3σ discovery potential to the $0\nu\beta\beta$ half-life of a nEXO-like experiment under a background consisting only of the $2\nu\beta\beta$ component.

Calculation	Reference	NME	$\overline{\langle m_{\beta\beta} \rangle}$
		$M_{0\nu}$	[meV]
IBM-2	[66]	3.05	9.0
Skyrme-QRPA	[65]	1.55	17.7
QRPA	[67]	2.46	11.1
RQRPA-UCOM	[68]	2.54	10.8
NREDF	[64]	4.77	5.7
REDF	[69]	4.32	6.3
ISM	[70]	1.77	15.5

TABLE VIII. Nuclear Matrix Elements (NME) values and corresponding 90% C.L. exclusion sensitivity limits on the Majorana neutrino mass $\langle m_{\beta\beta} \rangle$ for nEXO after 10 years of data taking. The values are computed for the ¹³⁶Xe $0\nu\beta\beta$ half-life sensitivity of 9.2×10^{27} years. (R)QRPA: (Renormalized) Quasi Random Phase Approximation; ISM: Interacting Shell Model; IBM: Interacting Boson Mode; (N)REDF: (Non)Relativistic Energy Density Functional. Majorana neutrino masses are computed assuming $g_A = 1.27$ [9].

converted into a reach on the effective Majorana neutrino mass $\langle m_{\beta\beta} \rangle$ under the assumption of a light Majorana neutrino exchange (Eq. (2)). Fig. 16 shows the nEXO exclusion sensitivity to $\langle m_{\beta\beta} \rangle$ as a function of the lightest neutrino mass. The allowed neutrino mass bands are derived from neutrino oscillation parameters from [62, 63]. The $\langle m_{\beta\beta} \rangle$ exclusion band between 5.7 and 17.7 meV arises from the range of nuclear matrix elements, with EDF [64] and QRPA [65] at the minimum and maximum extreme respectively. A detailed evaluation of the sensitivity for various NME choices is given in Table VIII. Majorana neutrino masses are computed assuming an axial-vector coupling constant of $g_A = 1.27$ [9].

Liquid xenon TPC is a proven, competitive technology in the search for $0\nu\beta\beta$. 3D event reconstruction in a monolithic detector at the tonne scale is a new power-




FIG. 16. 90% C.L. exclusion sensitivity reach to the effective majorana neutrino mass $m_{\beta\beta}$ as a function of the lightest neutrino mass for normal (left) and inverted (right) neutrino mass hierarchy. The width of the horizontal bands derive from the uncertainty in nuclear matrix elements (see text) and it assumes that $g_A = 1.27$. The width of the inner dashed bands result from the unknown Majorana phases and is irreducible. The outer solid lines incorporate the 90% CL errors of the 3-flavor neutrino fit of reference [62, 63].

ful tool to reject, and perhaps more importantly identify, backgrounds; this is especially important for a discovery-class experiment. Xenon is available at the tonne scale and is easily enriched thus simplifying the design and reducing the cost. The nEXO experiment is expected to increase the sensitivity to $0\nu\beta\beta$ by about two orders of magnitude over current experiments, and has the multiparameter dataset to make a convincing case for the discovery of the Majorana nature of the neutrino and the violation of lepton number.

ACKNOWLEDGMENTS

We gratefully acknowledge the support of SNOLAB for the gamma and radon assay work conducted on site. We thank Mitchell Negus for contributing to the simulation work. This work has been supported by the Offices of Nuclear and High Energy Physics within DOE's Office of Science, and NSF in the United States, by NERSC, CFI, FRQNT, NRC in Canada, by SNF in Switzerland, by IBS in Korea, by RFBR in Russia, and by CAS and ISTCP in China. This work was supported in part by Laboratory Directed Research and Development (LDRD) programs at Brookhaven National Laboratory (BNL), Lawrence Livermore National Laboratory (LLNL), Oak Ridge National Laboratory (ORNL), and Pacific Northwest National Laboratory (PNNL).

- [1] E. Majorana, Nuovo Cimento **14**, 171 (1937).
- [2] M. Fukugita and T. Yanagida, Phys. Lett. **B174**, 45 (1986).
- [3] Y. Fukuda *et al.* (Super-Kamiokande), Phys. Rev. Lett. **81**, 1562 (1998), arXiv:hep-ex/9807003 [hep-ex].
- [4] Q. R. Ahmad et al. (SNO), Phys. Rev. Lett. 89, 011301 (2002), arXiv:nucl-ex/0204008 [nucl-ex].
- [5] K. Eguchi et al. (KamLAND), Phys. Rev. Lett. 90, 021802 (2003), arXiv:hep-ex/0212021 [hep-ex].
- [6] F. T. Avignone, III, S. R. Elliott, and J. Engel, Rev. Mod. Phys. 80, 481 (2008), arXiv:0708.1033 [nucl-ex].
- [7] M. Agostini, G. Benato, and J. Detwiler, Phys. Rev. D96, 053001 (2017), arXiv:1705.02996 [hep-ex].
- [8] A. Caldwell, A. Merle, O. Schulz, and M. Totzauer, (2017), arXiv:1705.01945 [hep-ph].
- [9] C. Patrignani *et al.* (Particle Data Group), Chin. Phys. C40, 100001 (2016).
- [10] M. Redshaw, E. Wingfield, J. McDaniel, and E. G. Myers, Phys. Rev. Lett. 98, 053003 (2007).
- [11] P. M. McCowan and R. C. Barber, Phys. Rev. C82, 024603 (2010).
- [12] J. B. Albert et al. (EXO-200), Phys. Rev. C92, 015503 (2015), arXiv:1503.06241 [physics.ins-det].

- [13] J. B. Albert et al. (EXO-200), Nature 510, 229 (2014), arXiv:1402.6956 [nucl-ex].
- [14] M. Auger *et al.*, JINST **7**, P05010 (2012) arXiv:1202.2192 [physics.ins-det].
- [15] J. B. Albert et al. (EXO-200), Phys. Rev. C89, 015502 (2014), arXiv:1306.6106 [nucl-ex].
- [16] E. Aprile and T. Doke, Rev. Mod. Phys. 82, 2053 (2010), arXiv:0910.4956 [physics.ins-det].
- [17] A. Gando et al. (KamLAND-Zen), Phys. Rev. Lett. 117, 082503 (2016), [Addendum: Phys. Rev. Lett.117,no.10,109903(2016)], arXiv:1605.02889 [hep-ex].
- [18] J. B. Albert et al. (EXO-200), (2017), arXiv:1707.08707 [hep-ex].
- [19] E. Conti *et al.* (EXO-200), Phys. Rev. **B68**, 054201 (2003), arXiv:hep-ex/0303008 [hep-ex].
- [20] "3M HFE-7000," http://www.3m.com.
- [21] D. S. Leonard *et al.*, Nucl. Instrum. Meth. **A591**, 490 (2008), arXiv:0709.4524 [physics.ins-det].
- [22] D. S. Leonard et al., Nucl. Instrum. Meth. A871, 169 (2017), arXiv:1703.10799 [physics.ins-det].
- [23] J. B. Albert et al. (EXO-200), JCAP 04, 029 (2016), arXiv:1512.06835 [nucl-ex].
- [24] COMSOL©, http://www.comsol.com.

- [25] I. Ostrovskiy et al., IEEE Trans. Nucl. Sci. 62, 1825 (2015), arXiv:1502.07837 [physics.ins-det].
- [26] nEXO Collaboration, in preparation (2017).
- [27] "SNOLAB users handbook, revision 2," (2006).
- [28] S. Agostinelli et al. (GEANT4), Nucl. Instrum. Meth. A506, 250 (2003).
- [29] F. Boehm and P. Vogel, "Physics of massive neutrinos," (Cambridge University Press, 1992) pp. 141–151.
- [30] T. Böhlen, F. Cerutti, M. Chin, A. Fassò, A. Ferrari, P. Ortega, A. Mairani, P. Sala, G. Smirnov, and V. Vlachoudis, Nucl. Data Sheets 120, 211 (2014).
- [31] M. Auger et al. (EXO-200), Phys. Rev. Lett. 109, 032505 (2012), arXiv:1205.5608 [hep-ex].
- [32] M. Szydagis, A. Fyhrie, D. Thorngren, and M. Tripathi, Proceedings, LIght Detection In Noble Elements (LIDINE2013): Batavia, USA, May 29-31, 2013, JINST 8, C10003 (2013), arXiv:1307.6601 [physics.ins-det].
- [33] J. B. Albert et al. (EXO-200), Phys. Rev. C95, 025502 (2017), arXiv:1609.04467 [physics.ins-det].
- [34] W. Shockley, J. Appl. Phys. 9, 635 (1938).
- [35] S. Ramo, Proceedings of the IRE 27, 584 (1939).
- [36] J. B. Albert et al. (EXO-200), Phys. Rev. C92, 045504 (2015), arXiv:1506.00317 [nucl-ex].
- [37] J. Boger et al. (SNO), Nucl. Instrum. Meth. A449, 172 (2000), arXiv:nucl-ex/9910016 [nucl-ex].
- [38] I. Lawson, "Snolab-str-2007-003: Analysis of rock samples from the new laboratory,".
- [39] H.-S. Chen, Eur. Phys. J. Plus 127, 105 (2012).
- [40] L. Votano, Eur. Phys. J. Plus 127, 109 (2012).
- [41] K. T. Lesko et al., (2011), arXiv:1108.0959 [hep-ex].
- [42] K. T. Lesko, Eur. Phys. J. Plus 127, 107 (2012).
- [43] P. Vogel, "Solar neutrino background in EXO-200," EXO-200 Internal Note (2005).
- [44] H. Ejiri and S. R. Elliott, Phys. Rev. C89, 055501 (2014), arXiv:1309.7957 [nucl-ex].
- [45] N. F. de Barros and K. Zuber, J. Phys. G38, 105201 (2011), arXiv:1103.5757 [hep-ph].
- [46] P. Vogel, "Solar neutrino background in EXO-200," EXO-200 Internal Note (2012).
- [47] S. R. Elliott and H. Ejiri, in *Matrix Elements* for the *Double-beta-decay EXperiments* (MEDEX'17) Prague, Czech Republic, May 29-June 2, 2017 (2017) arXiv:1708.00927 [nucl-ex].
- [48] J. N. Bahcall, E. Lisi, D. E. Alburger, L. De Braeckeleer, S. J. Freedman, and J. Napolitano, Phys. Rev. C54, 411 (1996), arXiv:nucl-th/9601044 [nucl-th].
- [49] V. E. Guiseppe, S. R. Elliott, A. Hime, K. Rielage, and S. Westerdale, Proceedings, 3rd Topical Workshop on Low radioactivity techniques (LRT 2010): Sudbury, Canada, August 28-29, 2010, AIP Conf. Proc. 1338, 95 (2011),

- arXiv:1101.0126 [nucl-ex].
- [50] B. D. LaFerriere, T. C. Maiti, I. J. Arnquist, and E. W. Hoppe, Nucl. Instrum. Meth. A775, 93 (2015).
- [51] G. J. Feldman and R. D. Cousins, Phys. Rev. D57, 3873 (1998), arXiv:physics/9711021 [physics.data-an].
- [52] D. S. Akerib et al. (LZ), Submitted to: Astropart. Phys. (2017), arXiv:1702.02646 [physics.ins-det].
- [53] S. S. Wilks, Psychometrika 3, 23 (1938).
- [54] W. Verkerke and D. P. Kirkby, Statistical Problems in Particle Physics, Astrophysics and Cosmology (PHYS-TAT 05): Proceedings, Oxford, UK, September 12-15, 2005, eConf C0303241, MOLT007 (2003), [,186(2003)], arXiv:physics/0306116 [physics].
- [55] A. Lazzaro and L. Moneta, Proceedings, 17th International Conference on Computing in High Energy and Nuclear Physics (CHEP 2009): Prague, Czech Republic, March 21-27, 2009, J. Phys. Conf. Ser. 219, 042044 (2010).
- [56] F. Petry et al., Nucl. Instrum. Meth. A332, 107 (1993).
- [57] J. Hellmig and H. V. Klapdor-Kleingrothaus, Nucl. Instrum. Meth. A455, 638 (2000).
- [58] P. Ferrario et al. (NEXT), JHEP 01, 104 (2016), arXiv:1507.05902 [physics.ins-det].
- [59] A. S. Barabash, Nucl. Phys. A935, 52 (2015), arXiv:1501.05133 [nucl-ex].
- [60] K. Twelker et al., Rev. Sci. Instrum. 85, 095114 (2014), arXiv:1407.0618 [physics.ins-det].
- [61] B. Mong et al., Phys. Rev. A91, 022505 (2015), arXiv:1410.2624 [physics.atom-ph].
- [62] D. V. Forero, M. Tortola, and J. W. F. Valle, Phys. Rev. D90, 093006 (2014), arXiv:1405.7540 [hep-ph].
- [63] "Private communication with M. Tortola,".
- [64] N. L\(\tilde{A}\)spez Vaquero, T. R. Rodr\(\tilde{A}\)nguez, and J. L. Egido, Phys. Rev. Lett. 111, 142501 (2013), arXiv:1401.0650 [nucl-th].
- [65] M. T. Mustonen and J. Engel, Phys. Rev. C87, 064302 (2013), arXiv:1301.6997 [nucl-th].
- [66] J. Barea, J. Kotila, and F. Iachello, Phys. Rev. C91, 034304 (2015), arXiv:1506.08530 [nucl-th].
- [67] F. Šimkovic, V. Rodin, A. Faessler, and P. Vogel, Phys. Rev. C87, 045501 (2013), arXiv:1302.1509 [nucl-th].
- [68] A. Faessler, V. Rodin, and F. Šimkovic, J. Phys. G39, 124006 (2012), arXiv:1206.0464 [nucl-th].
- [69] J. M. Yao, L. S. Song, K. Hagino, P. Ring, and J. Meng, Phys. Rev. C91, 024316 (2015), arXiv:1410.6326 [nuclth].
- [70] J. Menéndez, A. Poves, E. Caurier, and F. Nowacki, Nucl. Phys. A818, 139 (2009), arXiv:0801.3760 [nucl-th].